


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id 426095-402344

Component

Diesel Engine

PETRO CANADA DURON SHP 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sample Number Client Info GFL0098307 GFL0079351 Info MAX Oil Age hrs Client Info 700 586 700 700 586 700 700 ACH Changed N/A Changed <th>2023 d L</th>	2023 d L
Sample Date Client Info 14 Nov 2023 02 Oct 2023 16 May Machine Age hrs Client Info 13285 13181 12595 Oil Age hrs Client Info 700 586 700 Oil Changed Client Info Changed N/A Changed Sample Status NORMAL NORMAL NORMAL NORMAL NORMAL CONTAMINATION method limit/base current history1 hist Fuel WC Method S <1.0 <1.0 0.6 Water WC Method >0.2 NEG NEG NEG Glycol WC Method NEG NEG NEG NEG WEAR METALS method limit/base current history1 hist Iron ppm ASTM D5185m >110 10 38 10 Chromium ppm ASTM D5185m >2 0 0 0 Titanium ppm ASTM D5185m >2 0 0 <1 Aluminum ppm ASTM D5185m >2 0 0 <1 Aluminum ppm ASTM D5185m >25 <1 1 2 Lead ppm ASTM D5185m >4 <1 1 2 Lead ppm ASTM D5185m >45 2 14 2 Copper ppm ASTM D5185m >4 <1 2 <1 Vanadium ppm ASTM D5185m >4 <1 2 <1 Vanadium ppm ASTM D5185m >4 <1 2 <1 Vanadium ppm ASTM D5185m 0 0 0 ADDITIVES method limit/base current history1 hist Darium ppm ASTM D5185m 0 0 0 0 ADDITIVES method limit/base current history1 hist Darium ppm ASTM D5185m 0 0 0 0 ADDITIVES method limit/base current history1 hist Darium ppm ASTM D5185m 0 0 0 0 ADDITIVES method limit/base current history1 hist Darium ppm ASTM D5185m 0 0 0 0 ADDITIVES method limit/base current history1 hist Darium ppm ASTM D5185m 0 0 0 0 0 ADDITIVES method limit/base current history1 hist Darium ppm ASTM D5185m 0 0 0 0 0 ADDITIVES method limit/base current history1 hist Darium ppm ASTM D5185m 0 0 0 0 0 ADDITIVES method limit/base current history1 hist Darium ppm ASTM D5185m 0 0 0 0 0 Darium ppm ASTM D5185m	2023 d L
Machine Age hrs Client Info 13285 13181 12595 Oil Age hrs Client Info 700 586 700 Oil Changed Client Info Changed N/A Changed Sample Status NORMAL NORMAL NORMAL NORMAL CONTAMINATION method limit/base current history1 hist Fuel WC Method >5 <1.0 <1.0 0.6 NEG Water WC Method >0.2 NEG NEG NEG NEG Glycol WC Method NEG NEG NEG NEG NEG WEAR METALS method limit/base current history1 hist Iron ppm ASTM D5185m >10 10 38 10 Chromium ppm ASTM D5185m >4 <1 1 1 Nickel ppm ASTM D5185m >2 0 0 <1 Silver	d L
Machine Age hrs Client Info 13285 13181 12595 Oil Age hrs Client Info 700 586 700 Oil Changed Client Info Changed N/A Change Sample Status Image: Client Info Changed N/A Change CONTAMINATION Image: Client Info MC Method NORMAL NORMAL NORMAL Fuel WC Method	d L
Oil Changed Sample Status Client Info Changed NORMAL N/A Changed NORMAL N/A Changed NORMAL N/A Changed NORMAL NORMAL </th <th>L</th>	L
NORMAL NORMAL NORMAL	L
CONTAMINATION method limit/base current history1 hist Fuel WC Method >5 <1.0 <1.0 0.6 Water WC Method >0.2 NEG NEG NEG Glycol WC Method NEG NEG NEG WEAR METALS method limit/base current history1 hist Iron ppm ASTM D5185m >110 10 38 10 Chromium ppm ASTM D5185m >4 <1 1 1 Nickel ppm ASTM D5185m >2 0 0 0 Silver ppm ASTM D5185m >2 0 0 <1 Aluminum ppm ASTM D5185m >2 0 0 <1 Lead ppm ASTM D5185m >45 2 14 2 Copper ppm ASTM D5185m >4 1 2 <1 <t< th=""><th></th></t<>	
Fuel WC Method >5 <1.0	ory2
Water WC Method >0.2 NEG NEG NEG Glycol WC Method NEG NEG NEG WEAR METALS method limit/base current history1 hist Iron ppm ASTM D5185m >110 10 38 10 Chromium ppm ASTM D5185m >4 <1	
Glycol WC Method NEG NEG NEG WEAR METALS method limit/base current history1 hist Iron ppm ASTM D5185m >110 10 38 10 Chromium ppm ASTM D5185m >4 <1 1 1 Nickel ppm ASTM D5185m >2 0 0 0 Silver ppm ASTM D5185m >2 0 0 <1 Silver ppm ASTM D5185m >2 0 0 <1 Aluminum ppm ASTM D5185m >2 0 0 <1 Lead ppm ASTM D5185m >45 2 14 2 Copper ppm ASTM D5185m >85 <1 2 <1 Tin ppm ASTM D5185m >4 <1 2 <1 Vanadium ppm ASTM D5185m 0 0 0 0 Cad	
WEAR METALS method limit/base current history1 hist Iron ppm ASTM D5185m >110 10 38 10 Chromium ppm ASTM D5185m >4 <1 1 1 Nickel ppm ASTM D5185m >2 0 0 0 Titanium ppm ASTM D5185m >2 0 0 <1 Silver ppm ASTM D5185m >2 0 0 <1 Aluminum ppm ASTM D5185m >2 0 0 <1 Aluminum ppm ASTM D5185m >25 <1 1 2 Lead ppm ASTM D5185m >45 2 14 2 Copper ppm ASTM D5185m >85 <1 2 <1 Tin ppm ASTM D5185m <1 0 0 0 Cadmium ppm ASTM D5185m 0 <1 <1 <td< th=""><th></th></td<>	
Iron	
Chromium ppm ASTM D5185m >4 <1	ory2
Nickel ppm ASTM D5185m >2 0 0 0 Titanium ppm ASTM D5185m 0 0 <1 Silver ppm ASTM D5185m >2 0 0 <1 Aluminum ppm ASTM D5185m >25 <1 1 2 Lead ppm ASTM D5185m >45 2 14 2 Copper ppm ASTM D5185m >85 <1 2 <1 Tin ppm ASTM D5185m >4 <1 2 <1 Vanadium ppm ASTM D5185m >4 <1 0 0 Cadmium ppm ASTM D5185m 0 0 0 0 ADDITIVES method limit/base current history1 hist Boron ppm ASTM D5185m 0 <1 <1 2 Barium ppm ASTM D5185m 0 0 0 0	
Titanium ppm ASTM D5185m 0 0 <1	
Silver ppm ASTM D5185m >2 0 0 <1	
Aluminum ppm ASTM D5185m >25 <1	
Lead ppm ASTM D5185m >45 2 14 2 Copper ppm ASTM D5185m >85 <1	
Copper ppm ASTM D5185m >85 <1	
Tin ppm ASTM D5185m >4 <1	
Vanadium ppm ASTM D5185m <1	
Cadmium ppm ASTM D5185m 0 0 0 ADDITIVES method limit/base current history1 hist Boron ppm ASTM D5185m 0 <1 <1 2 Barium ppm ASTM D5185m 0 0 0 0 Molybdenum ppm ASTM D5185m 60 59 66 66 Manganese ppm ASTM D5185m 0 <1 <1 <1 Magnesium ppm ASTM D5185m 1010 989 1032 1064 Calcium ppm ASTM D5185m 1070 1054 1135 1191 Phosphorus ppm ASTM D5185m 1150 1074 1062 1149	
ADDITIVES method limit/base current history1 hist Boron ppm ASTM D5185m 0 <1 <1 2 Barium ppm ASTM D5185m 0 0 0 0 Molybdenum ppm ASTM D5185m 60 59 66 66 Manganese ppm ASTM D5185m 0 <1 <1 <1 Magnesium ppm ASTM D5185m 1010 989 1032 1064 Calcium ppm ASTM D5185m 1070 1054 1135 1191 Phosphorus ppm ASTM D5185m 1150 1074 1062 1149	
Boron ppm ASTM D5185m 0 <1	
Barium ppm ASTM D5185m 0 0 0 0 Molybdenum ppm ASTM D5185m 60 59 66 66 Manganese ppm ASTM D5185m 0 <1 <1 <1 Magnesium ppm ASTM D5185m 1010 989 1032 1064 Calcium ppm ASTM D5185m 1070 1054 1135 1191 Phosphorus ppm ASTM D5185m 1150 1074 1062 1149	ory2
Molybdenum ppm ASTM D5185m 60 59 66 66 Manganese ppm ASTM D5185m 0 <1	
Manganese ppm ASTM D5185m 0 <1	
Magnesium ppm ASTM D5185m 1010 989 1032 1064 Calcium ppm ASTM D5185m 1070 1054 1135 1191 Phosphorus ppm ASTM D5185m 1150 1074 1062 1149	
Calcium ppm ASTM D5185m 1070 1054 1135 1191 Phosphorus ppm ASTM D5185m 1150 1074 1062 1149	
Phosphorus ppm ASTM D5185m 1150 1074 1062 1149	
7ino nom ASTM D5185m 1270 1274 1241 1202	
1 12 1	
Sulfur ppm ASTM D5185m 2060 3109 3057 3707	
CONTAMINANTS method limit/base current history1 hist	
Silicon ppm ASTM D5185m >30 3 5 4	Ji y Z
Sodium ppm ASTM D5185m 2 3 6	Jiyz
Potassium ppm ASTM D5185m >20 0 0 2	J1 y Z
·	
Soot % % *ASTM D7844 >3 0.2 0.7 0.5	ory2
Nitration Abs/cm *ASTM D7624 >20 6.8 10.6 9.8	
Sulfation Abs/.1mm *ASTM D7415 >30 19.0 22.4 21.6	
FLUID DEGRADATION method limit/base current history1 hist	
Oxidation Abs/.1mm *ASTM D7414 >25 15.3 20.2 17.9	ory2
Base Number (BN) mg KOH/g ASTM D2896 9.8 8.5 7.6 8.0	ory2



OIL ANALYSIS REPORT








VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROPI	ERTIES	method				history2
Visc @ 100°C	cSt	ASTM D445	15.4	12.5	12.8	13.7

GRAPHS













Certificate L2367

Laboratory Sample No. Lab Number Test Package : FLEET

Unique Number : 10751104

: GFL0098307 : 06011960

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 20 Nov 2023

: 21 Nov 2023 Diagnosed Diagnostician : Wes Davis

GFL Environmental - 822 - Springfield Hauling

2120 West Bennett Street Springfield, MO US 65807

Contact: Dennis Moore dennis.moore@gflenv.com T: (417)403-3641

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)