


# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Area  
**KEMP QUARRIES / BCS - GRAVETTE [65546]**  
Machine Id  
**OHT107**  
Component  
**Transmission (Auto)**  
Fluid  
**PETRO CANADA PRODURO TO-4 SAE 30 (--- GAL)**



## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. ( Customer Sample Comment: PM-3 changed filters )

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The condition of the oil is acceptable for the time in service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>PCA0087034</b>	PCA0085724	PCA0086703
Sample Date	Client Info		<b>30 Oct 2023</b>	12 May 2023	26 Jan 2023
Machine Age	hrs	Client Info	<b>25681</b>	25099	24569
Oil Age	hrs	Client Info	<b>25681</b>	25099	24569
Oil Changed	Client Info		<b>N/A</b>	Changed	N/A
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.1	<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >160	<b>5</b>	6	6
Chromium	ppm	ASTM D5185m >5	<b>0</b>	<1	<1
Nickel	ppm	ASTM D5185m >5	<b>0</b>	0	<1
Titanium	ppm	ASTM D5185m	<b>0</b>	0	0
Silver	ppm	ASTM D5185m >5	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >50	<b>6</b>	0	0
Lead	ppm	ASTM D5185m >50	<b>1</b>	1	2
Copper	ppm	ASTM D5185m >225	<b>7</b>	9	9
Tin	ppm	ASTM D5185m >10	<b>0</b>	0	<1
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	<b>0</b>	1	2
Barium	ppm	ASTM D5185m 0	<b>0</b>	11	0
Molybdenum	ppm	ASTM D5185m 0	<b>&lt;1</b>	2	2
Manganese	ppm	ASTM D5185m 9	<b>0</b>	<1	<1
Magnesium	ppm	ASTM D5185m 1	<b>19</b>	39	30
Calcium	ppm	ASTM D5185m 3131	<b>2609</b>	2637	2892
Phosphorus	ppm	ASTM D5185m 1194	<b>922</b>	891	951
Zinc	ppm	ASTM D5185m 1281	<b>1158</b>	1038	1158
Sulfur	ppm	ASTM D5185m 3811	<b>3612</b>	3895	4383


## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >20	<b>16</b>	5	5
Sodium	ppm	ASTM D5185m	<b>1</b>	2	2
Potassium	ppm	ASTM D5185m >20	<b>0</b>	0	0

## VISUAL

	method	limit/base	current	history1	history2
White Metal	scalar	*Visual NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual NONE	<b>NONE</b>	NONE	NONE
Precipitate	scalar	*Visual NONE	<b>NONE</b>	NONE	NONE
Silt	scalar	*Visual NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual >0.1	<b>NEG</b>	NEG	NEG
Free Water	scalar	*Visual	<b>NEG</b>	NEG	NEG









# OIL ANALYSIS REPORT



FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	88.5	<b>91.9</b>	87.9	88.0

SAMPLE IMAGES		method	limit/base	current	history1	history2
Color				no image	no image	no image
Bottom				no image	no image	no image

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0087034 **Received** : 20 Nov 2023  
**Lab Number** : 06013583 **Diagnosed** : 22 Nov 2023  
**Unique Number** : 10752727 **Diagnostician** : Sean Felton  
**Test Package** : MOB 1

**Kemp Quarries - Benton County Stone - Gravette**  
 15100 N Hwy 59  
 Sulphur Springs, AR  
 US 72768  
 Contact:  
 gravette@bentoncountystone.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: