




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**11267**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (16 GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

|               | method      | limit/base  | current            | history1    | history2    |
|---------------|-------------|-------------|--------------------|-------------|-------------|
| Sample Number | Client Info |             | <b>GFL0097181</b>  | GFL0097215  | GFL0069203  |
| Sample Date   | Client Info |             | <b>16 Nov 2023</b> | 27 Oct 2023 | 14 Sep 2023 |
| Machine Age   | hrs         | Client Info | <b>11835</b>       | 11688       | 11448       |
| Oil Age       | hrs         | Client Info | <b>147</b>         | 624         | 384         |
| Oil Changed   | Client Info |             | <b>Not Changed</b> | Changed     | Not Changed |
| Sample Status |             |             | <b>NORMAL</b>      | NORMAL      | NORMAL      |

## CONTAMINATION

|        | method    | limit/base | current        | history1 | history2 |
|--------|-----------|------------|----------------|----------|----------|
| Fuel   | WC Method | >5         | <b>&lt;1.0</b> | <1.0     | <1.0     |
| Water  | WC Method | >0.2       | <b>NEG</b>     | NEG      | NEG      |
| Glycol | WC Method |            | <b>NEG</b>     | NEG      | NEG      |

## WEAR METALS

|          | method | limit/base       | current      | history1 | history2 |
|----------|--------|------------------|--------------|----------|----------|
| Iron     | ppm    | ASTM D5185m >100 | <b>21</b>    | 12       | 18       |
| Chromium | ppm    | ASTM D5185m >20  | <b>&lt;1</b> | <1       | 1        |
| Nickel   | ppm    | ASTM D5185m >4   | <b>0</b>     | 0        | <1       |
| Titanium | ppm    | ASTM D5185m      | <b>&lt;1</b> | 0        | <1       |
| Silver   | ppm    | ASTM D5185m >3   | <b>&lt;1</b> | 0        | 0        |
| Aluminum | ppm    | ASTM D5185m >20  | <b>4</b>     | 2        | 5        |
| Lead     | ppm    | ASTM D5185m >40  | <b>&lt;1</b> | 0        | 1        |
| Copper   | ppm    | ASTM D5185m >330 | <b>2</b>     | 2        | 12       |
| Tin      | ppm    | ASTM D5185m >15  | <b>&lt;1</b> | <1       | 1        |
| Vanadium | ppm    | ASTM D5185m      | <b>0</b>     | 0        | <1       |
| Cadmium  | ppm    | ASTM D5185m      | <b>0</b>     | 0        | 0        |

## ADDITIVES

|            | method | limit/base       | current     | history1 | history2 |
|------------|--------|------------------|-------------|----------|----------|
| Boron      | ppm    | ASTM D5185m 0    | <b>5</b>    | 3        | 7        |
| Barium     | ppm    | ASTM D5185m 0    | <b>0</b>    | 0        | 0        |
| Molybdenum | ppm    | ASTM D5185m 60   | <b>79</b>   | 60       | 97       |
| Manganese  | ppm    | ASTM D5185m 0    | <b>0</b>    | <1       | <1       |
| Magnesium  | ppm    | ASTM D5185m 1010 | <b>1169</b> | 919      | 1411     |
| Calcium    | ppm    | ASTM D5185m 1070 | <b>1274</b> | 1048     | 1579     |
| Phosphorus | ppm    | ASTM D5185m 1150 | <b>1265</b> | 1095     | 1478     |
| Zinc       | ppm    | ASTM D5185m 1270 | <b>1509</b> | 1180     | 1848     |
| Sulfur     | ppm    | ASTM D5185m 2060 | <b>3887</b> | 2916     | 5027     |

## CONTAMINANTS

|           | method | limit/base      | current  | history1 | history2 |
|-----------|--------|-----------------|----------|----------|----------|
| Silicon   | ppm    | ASTM D5185m >25 | <b>8</b> | 6        | 11       |
| Sodium    | ppm    | ASTM D5185m     | <b>2</b> | 3        | 3        |
| Potassium | ppm    | ASTM D5185m >20 | <b>2</b> | 2        | <1       |

## INFRA-RED



|           | method   | limit/base      | current     | history1 | history2 |
|-----------|----------|-----------------|-------------|----------|----------|
| Soot %    | %        | *ASTM D7844 >3  | <b>1.1</b>  | 0.9      | 0.7      |
| Nitration | Abs/cm   | *ASTM D7624 >20 | <b>11.1</b> | 9.8      | 8.4      |
| Sulfation | Abs/.1mm | *ASTM D7415 >30 | <b>20.6</b> | 19.9     | 19.0     |

## FLUID DEGRADATION

|                  | method   | limit/base      | current     | history1 | history2 |
|------------------|----------|-----------------|-------------|----------|----------|
| Oxidation        | Abs/.1mm | *ASTM D7414 >25 | <b>17.0</b> | 16.1     | 14.8     |
| Base Number (BN) | mg KOH/g | ASTM D2896 9.8  | <b>9.0</b>  | 8.8      | 8.9      |







# OIL ANALYSIS REPORT



| VISUAL           | method | limit/base | current | history1 | history2 |
|------------------|--------|------------|---------|----------|----------|
| White Metal      | scalar | *Visual    | NONE    | NONE     | NONE     |
| Yellow Metal     | scalar | *Visual    | NONE    | NONE     | NONE     |
| Precipitate      | scalar | *Visual    | NONE    | NONE     | NONE     |
| Silt             | scalar | *Visual    | NONE    | NONE     | NONE     |
| Debris           | scalar | *Visual    | NONE    | NONE     | NONE     |
| Sand/Dirt        | scalar | *Visual    | NONE    | NONE     | NONE     |
| Appearance       | scalar | *Visual    | NORML   | NORML    | NORML    |
| Odor             | scalar | *Visual    | NORML   | NORML    | NORML    |
| Emulsified Water | scalar | *Visual    | >0.2    | NEG      | NEG      |
| Free Water       | scalar | *Visual    |         | NEG      | NEG      |

| FLUID PROPERTIES | method | limit/base | current | history1    | history2 |      |
|------------------|--------|------------|---------|-------------|----------|------|
| Visc @ 100°C     | cSt    | ASTM D445  | 15.4    | <b>13.6</b> | 13.6     | 13.7 |

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0097181 **Received** : 24 Nov 2023  
**Lab Number** : **06016228** **Diagnosed** : 26 Nov 2023  
**Unique Number** : 10755372 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 073 - Warner Robins - Transwaste**  
 155 Story Road  
 Warner Robins, GA  
 US 31093  
 Contact: JOSH MALONEY  
 jmaloney@gflenv.com  
 T:  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)