

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL


Machine Id
126
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 10W30 (--- GAL)



DIAGNOSIS

Recommendation
 Resample at the next service interval to monitor.

Wear
 Metal levels are typical for a new component breaking in.

Contamination
 There is no indication of any contamination in the oil.

Fluid Condition
 The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0110777	---	---
Sample Date	Client Info		16 Nov 2023	---	---
Machine Age	mls Client Info		21311	---	---
Oil Age	mls Client Info		21311	---	---
Oil Changed	Client Info		Changed	---	---
Sample Status			NORMAL	---	---

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	---	---
Water	WC Method	>0.2	NEG	---	---
Glycol	WC Method		NEG	---	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m	>100	42	---	---
Chromium	ppm ASTM D5185m	>20	4	---	---
Nickel	ppm ASTM D5185m	>4	1	---	---
Titanium	ppm ASTM D5185m		<1	---	---
Silver	ppm ASTM D5185m	>3	1	---	---
Aluminum	ppm ASTM D5185m	>20	24	---	---
Lead	ppm ASTM D5185m	>40	2	---	---
Copper	ppm ASTM D5185m	>330	14	---	---
Tin	ppm ASTM D5185m	>15	3	---	---
Vanadium	ppm ASTM D5185m		<1	---	---
Cadmium	ppm ASTM D5185m		0	---	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m	2	20	---	---
Barium	ppm ASTM D5185m	0	0	---	---
Molybdenum	ppm ASTM D5185m	50	9	---	---
Manganese	ppm ASTM D5185m	0	2	---	---
Magnesium	ppm ASTM D5185m	950	760	---	---
Calcium	ppm ASTM D5185m	1050	1268	---	---
Phosphorus	ppm ASTM D5185m	995	807	---	---
Zinc	ppm ASTM D5185m	1180	883	---	---
Sulfur	ppm ASTM D5185m	2600	2942	---	---

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m	>25	17	---	---
Sodium	ppm ASTM D5185m		4	---	---
Potassium	ppm ASTM D5185m	>20	58	---	---



INFRA-RED

	method	limit/base	current	history1	history2
Soot %	% *ASTM D7844	>3	0.3	---	---
Nitration	Abs/cm *ASTM D7624	>20	10.2	---	---
Sulfation	Abs/.1mm *ASTM D7415	>30	23.2	---	---

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414	>25	19.2	---	---
Base Number (BN)	mg KOH/g ASTM D2896		5.5	---	---





OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.7	---

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0110777 **Received** : 27 Nov 2023
Lab Number : 06017692 **Diagnosed** : 29 Nov 2023
Unique Number : 10756836 **Diagnostician** : Sean Felton
Test Package : FLEET

BLUE MAX TRUCKING
 1015 E. WESTINGHOUSE BLVD.
 CHARLOTTE, NC
 US 28273
 Contact: Jody Greer
 jgreer@bluemaxtrucking.com
 T: (980)225-9968
 F: (704)588-2901

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)