


OIL ANALYSIS REPORT

No Info On Sample [No Info On Sample] NOT GIVEN PCA0112883

Diesel Engine

NOT GIVEN (--- GAL)





DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

				Nov2023		
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0112883		
Sample Date		Client Info		26 Nov 2023		
Machine Age	mls	Client Info		0		
Oil Age	mls	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINAT	ION	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0		
Water		WC Method	>0.2	NEG		
Glycol		WC Method		NEG		
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	17		
Chromium	ppm	ASTM D5185m	>20	<1		
Nickel	ppm	ASTM D5185m	>4	3		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m	>3	0		
Aluminum	ppm	ASTM D5185m	>20	4		
Lead	ppm	ASTM D5185m	>40	<1		
Copper	ppm	ASTM D5185m	>330	0		
Tin	ppm	ASTM D5185m	>15	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		2		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		52		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		860		
Calcium	ppm	ASTM D5185m		953		
Phosphorus	ppm	ASTM D5185m		1034		
Zinc	ppm	ASTM D5185m		1171		
Sulfur	ppm	ASTM D5185m		2941		
CONTAMINAN	ITS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	4		
Sodium	ppm	ASTM D5185m		2		
Potassium	ppm	ASTM D5185m	>20	2		
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.9		
Nitration	Abs/cm	*ASTM D7624	>20	9.2		
Sulfation	Abs/.1mm	*ASTM D7415	>30	24.0		
FLUID DEGRAI	OITAC	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	24.9		
	mg KOH/g	ASTM D2896		7.2		




OIL ANALYSIS REPORT





VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.2	NEG		
Free Water	scalar	*Visual		NEG		


	LITTLO	memou		Thistory I	HISTOLYZ
Visc @ 100°C	cSt	ASTM D445	13.3		

GRAPHS













Certificate L2367

Laboratory Sample No. Lab Number Unique Number : 10756846 Test Package : FLEET

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : PCA0112883 : 06017702

To discuss this sample report, contact Customer Service at 1-800-237-1369.

Received Diagnosed Diagnostician : Wes Davis

: 27 Nov 2023 : 28 Nov 2023

Transervice - Shop 1364 - Berkeley-Mt. Vernon

5100 Lake Terrace NE Mt. Vernon, IL US 62864 Contact: Erien White

ewhite@transervice.com T: (618)244-8726

F: (618)244-8791

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)