




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**425041-402302**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0103477</b>	GFL0094824	GFL0094813
Sample Date	Client Info		<b>24 Nov 2023</b>	09 Oct 2023	15 Sep 2023
Machine Age	hrs	Client Info	<b>18265</b>	18078	17944
Oil Age	hrs	Client Info	<b>946</b>	759	625
Oil Changed	Client Info		<b>Changed</b>	N/A	N/A
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	<b>16</b>	15	12
Chromium	ppm	ASTM D5185m >20	<b>&lt;1</b>	2	<1
Nickel	ppm	ASTM D5185m >5	<b>0</b>	<1	<1
Titanium	ppm	ASTM D5185m >2	<b>0</b>	<1	<1
Silver	ppm	ASTM D5185m >2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >20	<b>10</b>	15	12
Lead	ppm	ASTM D5185m >40	<b>&lt;1</b>	1	<1
Copper	ppm	ASTM D5185m >330	<b>3</b>	4	3
Tin	ppm	ASTM D5185m >15	<b>0</b>	<1	<1
Vanadium	ppm	ASTM D5185m	<b>0</b>	<1	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	<1	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>0</b>	2	4
Barium	ppm	ASTM D5185m 0	<b>2</b>	10	0
Molybdenum	ppm	ASTM D5185m 60	<b>59</b>	76	64
Manganese	ppm	ASTM D5185m 0	<b>0</b>	<1	<1
Magnesium	ppm	ASTM D5185m 1010	<b>868</b>	1149	1014
Calcium	ppm	ASTM D5185m 1070	<b>992</b>	1203	1118
Phosphorus	ppm	ASTM D5185m 1150	<b>892</b>	1237	1097
Zinc	ppm	ASTM D5185m 1270	<b>1117</b>	1458	1316
Sulfur	ppm	ASTM D5185m 2060	<b>2645</b>	3738	3847

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>10</b>	11	9
Sodium	ppm	ASTM D5185m	<b>3</b>	4	6
Potassium	ppm	ASTM D5185m >20	<b>2</b>	3	2

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	<b>0.1</b>	0.1	0.1
Nitration	Abs/cm	*ASTM D7624 >20	<b>9.4</b>	8.4	7.7
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>21.2</b>	19.4	17.9

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>17.9</b>	16.2	14.7
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>4.5</b>	5.5	7.0







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>12.9</b>	13.3	13.4

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0103477 **Received** : 05 Dec 2023  
**Lab Number** : **06025616** **Diagnosed** : 06 Dec 2023  
**Unique Number** : 10770116 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 868 - Childersburg Fines Hauling (Alpine)**  
 13737 Plant Rd  
 Childersburg, AL  
 US 35044  
**Contact: JONATHAN WILLIAMS**  
 jonathan.williams@gflenv.com  
 T:  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)