




PROBLEM SUMMARY

Sample Rating Trend



FUEL




Machine Id
828044-Pete 520

Component
Diesel Engine

Fluid
PETRO CANADA DURON SHP 15W40 (42 QTS)

COMPONENT CONDITION SUMMARY

▲ Fuel Dilution



RECOMMENDATION

The oil change at the time of sampling has been noted. Resample at the next service interval to monitor. No other corrective action is recommended at this time.

PROBLEMATIC TEST RESULTS

Sample Status				MARGINAL	ABNORMAL	MARGINAL
Fuel	%	ASTM D3524	>3.0	▲ 1.1	▲ 3.5	0.2

Customer Id: GFL656
Sample No.: GFL0096491
Lab Number: 06027017
Test Package: FLEET



To manage this report scan the QR code

To discuss the diagnosis or test data:
Wes Davis +1 905-569-8600 x223
wesd@wearcheck.ca

To change component or sample information:
Customer Service +1 1-800-237-1369
customerservice@wearcheck.com

RECOMMENDED ACTIONS

There are no recommended actions for this sample.

HISTORICAL DIAGNOSIS

15 Jun 2023 Diag: Wes Davis

FUEL



The oil change at the time of sampling has been noted. We recommend an early resample to monitor this condition. All component wear rates are normal. There is a moderate amount of fuel present in the oil. Tests confirm the presence of fuel in the oil. The BN result indicates that there is suitable alkalinity remaining in the oil. Fuel is present in the oil and is lowering the viscosity. The oil is no longer serviceable due to the presence of contaminants.

view report



17 Apr 2023 Diag: Jonathan Hester

VISCOSITY



Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor. All component wear rates are normal. Fuel content negligible. There is no indication of any contamination in the oil. The oil viscosity is lower than normal. The BN result indicates that there is suitable alkalinity remaining in the oil.


view report





OIL ANALYSIS REPORT

Sample Rating Trend



FUEL



Machine Id
828044-Pete 520

Component
Diesel Engine

Fluid
PETRO CANADA DURON SHP 15W40 (42 QTS)

DIAGNOSIS

Recommendation

The oil change at the time of sampling has been noted. Resample at the next service interval to monitor. No other corrective action is recommended at this time.

Wear

All component wear rates are normal.

Contamination

Light fuel dilution occurring. No other contaminants were detected in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0096491	GFL0062010	GFL0061964
Sample Date	Client Info	20 Nov 2023	15 Jun 2023	17 Apr 2023
Machine Age	hrs	11256	10768	10408
Oil Age	hrs	488	360	600
Oil Changed	Client Info	Changed	Changed	Changed
Sample Status		MARGINAL	ABNORMAL	MARGINAL

CONTAMINATION

method	limit/base	current	history1	history2
Water	WC Method >0.2	NEG	NEG	NEG
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >90	9	20	17
Chromium	ppm ASTM D5185m >20	<1	1	<1
Nickel	ppm ASTM D5185m >2	<1	<1	0
Titanium	ppm ASTM D5185m >2	0	<1	5
Silver	ppm ASTM D5185m >2	0	<1	0
Aluminum	ppm ASTM D5185m >20	<1	<1	0
Lead	ppm ASTM D5185m >40	1	3	2
Copper	ppm ASTM D5185m >330	7	1	<1
Tin	ppm ASTM D5185m >15	<1	1	<1
Vanadium	ppm ASTM D5185m	<1	<1	0
Cadmium	ppm ASTM D5185m	0	<1	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	15	21	18
Barium	ppm ASTM D5185m 0	0	1	2
Molybdenum	ppm ASTM D5185m 60	55	67	60
Manganese	ppm ASTM D5185m 0	0	<1	<1
Magnesium	ppm ASTM D5185m 1010	919	1078	856
Calcium	ppm ASTM D5185m 1070	1105	1259	1121
Phosphorus	ppm ASTM D5185m 1150	963	1103	994
Zinc	ppm ASTM D5185m 1270	1239	1422	1228
Sulfur	ppm ASTM D5185m 2060	2536	3861	3085

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	6	9	6
Sodium	ppm ASTM D5185m	8	10	4
Potassium	ppm ASTM D5185m >20	3	15	4
Fuel	% ASTM D3524 >3.0	▲ 1.1	▲ 3.5	0.2

INFRA-RED




method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >6	0.4	0.3	0.4
Nitration	Abs/cm *ASTM D7624 >20	8.5	8.5	8.3
Sulfation	Abs/.1mm *ASTM D7415 >30	19.6	19.9	17.8

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	15.5	14.9	14.6
Base Number (BN)	mg KOH/g ASTM D2896 9.8	7.5	8.9	6.5







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	13.5	▲ 12.0 ▲ 12.4

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0096491 **Received** : 06 Dec 2023
Lab Number : **06027017** **Diagnosed** : 14 Dec 2023
Unique Number : 10776808 **Diagnostician** : Wes Davis
Test Package : FLEET (Additional Tests: PercentFuel)

GFL Environmental - 656 - Culpeper Hauling
 15490 Montanus Drive
 Culpeper, VA
 US 22701
 Contact: Matt Hanna
 mhanna@gflenv.com
 T: (540)727-0887
 F:

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)