


OIL ANALYSIS REPORT



KENWORTH 421068

Component

Diesel Engine

PETRO CANADA DURON SHP 15W40 (--- QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil


Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

QTS)				Dec2023		
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
	WIATION	Client Info	mmodasc	GFL0091674		matoryz
Sample Number Sample Date		Client Info		01 Dec 2023		
Machine Age	hrs	Client Info		2591		
Oil Age	hrs	Client Info		0		
Oil Changed	1113	Client Info		Changed		
Sample Status		Oliciti IIIIo		NORMAL		
CONTAMINAT	ION	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0		
Water		WC Method	>0.2	NEG		
Glycol		WC Method		NEG		
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	18		
Chromium	ppm	ASTM D5185m	>20	<1		
Nickel	ppm	ASTM D5185m	>4	0		
Titanium	ppm	ASTM D5185m	- 1	<1		
Silver	ppm	ASTM D5185m	>3	0		
Aluminum	ppm	ASTM D5185m	>20	1		
Lead	ppm	ASTM D5185m	>40	<1		
Copper	ppm	ASTM D5185m	>330	3		
Tin	ppm	ASTM D5185m	>15	0		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	14		
Barium	ppm	ASTM D5185m	0	0		
Molybdenum	ppm	ASTM D5185m	60	58		
Manganese	ppm	ASTM D5185m	0	<1		
Magnesium	ppm	ASTM D5185m	1010	921		
Calcium	ppm	ASTM D5185m	1070	1260		
Phosphorus	ppm	ASTM D5185m	1150	1042		
Zinc	ppm	ASTM D5185m	1270	1245		
Sulfur	ppm	ASTM D5185m	2060	3173		
CONTAMINAN	ITS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	5		
Sodium	ppm	ASTM D5185m		2		
Potassium	ppm	ASTM D5185m	>20	<1		
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.3		
Nitration	Abs/cm	*ASTM D7624	>20	8.3		
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.5		
FLUID DEGRAI	DATION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	16.1		
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	8.6		




OIL ANALYSIS REPORT





VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.2	NEG		
Free Water	scalar	*Visual		NEG		
	DTIEO	اء مالم مما	lineit/lenen		hinton d	history O


FLUID FNOF		memod			HISTOLAL	HISTORY
Visc @ 100°C	cSt	ASTM D445	15.4	13.6		

GRAPHS











Certificate L2367

Laboratory Sample No. Lab Number Unique Number : 10776918 Test Package : FLEET

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : GFL0091674 : 06027127

Diagnosed

Received : 06 Dec 2023 : 11 Dec 2023 Diagnostician : Jonathan Hester GFL Environmental - 036 - North Wilksboro 489 Boone Trail

Wilkesboro, NC US 28659

Contact: JAMES KRESGE

jkresge@gflenv.com

T: F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)