PROBLEM SUMMARY

Sample Rating Trend
SEDIMENT

Machine Id 928088-260340 Component Transmission Fluid NOT GIVEN (--- GAL)

COMPONENT CONDITION SUMMARY

No relevant graphs to display

	Sampla Statua	
RECOMMENDATION	PROBLEMATIC TEST RESULTS	

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

PROBLEMATIC	C TEST	RESULT	S		
Sample Status				ABNORMAL	
Silt	scalar	*Visual	NONE	A MODER	

Customer Id: GFL837 Sample No.: GFL0102550 Lab Number: 06027254 Test Package: FLEET



To manage this report scan the QR code

To discuss the diagnosis or test data: Don Baldridge +1 <u>don.b505@comcast.net</u>

To change component or sample information: Customer Service +1 1-800-237-1369 <u>customerservice@wearcheck.com</u>

RECOMMENDED ACTIONS						
Action	Status	Date	Done By	Description		
Change Fluid			?	Oil and filter change at the time of sampling has been noted.		
Change Filter			?	Oil and filter change at the time of sampling has been noted.		

HISTORICAL DIAGNOSIS



OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id 928088-260340

Component Transmission Fluid NOT GIVEN (--- GAL)

DIAGNOSIS

A Recommendation

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

Moderate concentration of visible dirt/debris present in the fluid.

Fluid Condition

The condition of the fluid is acceptable for the time in service.

SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0102550		
Sample Date		Client Info		28 Nov 2023		
	hrs	Client Info		13865		
Ũ	hrs	Client Info		0		
Oil Changed		Client Info		Changed		
Sample Status				ABNORMAL		
CONTAMINATIC)N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron p	ppm	ASTM D5185m	>200	22		
	ppm	ASTM D5185m	>10	<1		
	ppm	ASTM D5185m		0		
	ppm	ASTM D5185m		<1		
1		ASTM D5185m		0		
1	ppm	ASTM D5185m	>50	2		
		ASTM D5185m	>50 >50	2 <1		
	ppm			2		
	ppm	ASTM D5185m ASTM D5185m		2		
1	ppm		>10	-		
	ppm	ASTM D5185m		0		
-	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron p	ppm	ASTM D5185m		81		
Barium p	ppm	ASTM D5185m		0		
Molybdenum p	ppm	ASTM D5185m		<1		
Manganese p	ppm	ASTM D5185m		0		
Magnesium p	ppm	ASTM D5185m		5		
Calcium p	ppm	ASTM D5185m		145		
Phosphorus p	ppm	ASTM D5185m		232		
Zinc p	ppm	ASTM D5185m		5		
Sulfur r				Э		
	ppm	ASTM D5185m		5 2092		
			limit/base	-		
CONTAMINANT	S	ASTM D5185m	limit/base	2092		
CONTAMINANT: Silicon	S ppm	ASTM D5185m method ASTM D5185m		2092 current 12		
CONTAMINANT Silicon F Sodium F	S	ASTM D5185m method		2092 current	 history1 	 history2
CONTAMINANT Silicon F Sodium F	S ppm ppm	ASTM D5185m method ASTM D5185m ASTM D5185m	>50	2092 current 12 <1	 history1 	 history2
CONTAMINANT Silicon p Sodium p Potassium p VISUAL	S ppm ppm	ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m	>50 >20	2092 current 12 <1 1	 history1 	 history2
CONTAMINANT Silicon p Sodium p Potassium p VISUAL	S opm opm opm	ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m method	>50 >20 limit/base	2092 current 12 <1 1 current	 history1 history1	history2 history2
CONTAMINANT Silicon p Sodium p Potassium p VISUAL White Metal s Yellow Metal s	S ppm ppm ppm scalar	ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m method *Visual	>50 >20 limit/base NONE	2092 current 12 <1 1 current NONE	 history1 history1 	<pre> history2 history2 history2 history2</pre>
CONTAMINANT Silicon p Sodium p Potassium p VISUAL White Metal s Yellow Metal s Precipitate	S ppm ppm ppm scalar scalar	ASTM D5185m Method ASTM D5185m ASTM D5185m Method *Visual *Visual	>50 >20 limit/base NONE NONE	2092 current 12 <1 1 current NONE NONE	 history1 history1 	 history2 history2
CONTAMINANT Silicon p Sodium p Potassium p VISUAL v White Metal s Yellow Metal s Precipitate s Silt s	S ppm ppm ppm scalar scalar scalar	ASTM D5185m Method ASTM D5185m ASTM D5185m Method *Visual *Visual *Visual	>50 >20 limit/base NONE NONE NONE	2092 current 12 <1 1 current NONE NONE NONE	 history1 history1 	 history2 history2
CONTAMINANT Silicon p Sodium p Potassium p VISUAL v White Metal s Yellow Metal s Precipitate s Silt s	S ppm ppm ppm scalar scalar scalar scalar	ASTM D5185m Method ASTM D5185m ASTM D5185m *Visual *Visual *Visual *Visual *Visual *Visual	>50 >20 limit/base NONE NONE NONE NONE NONE	2092 current 12 <1 1 current NONE NONE NONE NONE NONE NONE NONE	 history1 history1 	 history2 history2
CONTAMINANT Silicon p Sodium p Potassium p VISUAL v White Metal s Yellow Metal s Precipitate s Silt s Debris s Sand/Dirt s	S ppm ppm scalar scalar scalar scalar scalar scalar	ASTM D5185m Method ASTM D5185m ASTM D5185m *Visual *Visual *Visual *Visual *Visual *Visual *Visual *Visual	>50 >20 Iimit/base NONE NONE NONE NONE NONE	2092 current 12 <1 1 current NONE NONE NONE NONE NONE NONE NONE	 history1 history1 	 history2 history2
CONTAMINANT Silicon p Sodium p Potassium p VISUAL v White Metal s Yellow Metal s Precipitate s Silt s Debris s Sand/Dirt s	S ppm ppm scalar scalar scalar scalar scalar scalar scalar scalar scalar	ASTM D5185m Method ASTM D5185m ASTM D5185m *Visual *Visual *Visual *Visual *Visual *Visual *Visual *Visual *Visual *Visual	>50 >20 Imit/base NONE NONE NONE NONE NONE NONE NONE NONE	2092 current 12 <1 1 current NONE NONE NONE NONE NONE NONE NONE NONE NONE NONE	 history1 history1 	 history2 history2
CONTAMINANT Silicon p Sodium p Potassium p VISUAL v White Metal s Yellow Metal s Precipitate s Silt s Debris s Sand/Dirt s Appearance s	S ppm ppm scalar scalar scalar scalar scalar scalar scalar scalar scalar	ASTM D5185m Method ASTM D5185m ASTM D5185m *Visual *Visual *Visual *Visual *Visual *Visual *Visual *Visual *Visual *Visual	>50 20 Imit/base NONE NONE NONE NONE NONE NONE NONE NON	2092 current 12 <1 1 current NONE NONE NONE NONE NONE NONE NONE NONE NONE NONE NONE	 history1 history1 	 history2 history2
CONTAMINANT Silicon p Sodium p Potassium p VISUAL v White Metal s Yellow Metal s Yellow Metal s Silt s Debris s Sand/Dirt s Appearance s Odor s Emulsified Water s	S ppm ppm scalar scalar scalar scalar scalar scalar scalar scalar scalar	ASTM D5185m Method ASTM D5185m ASTM D5185m *Visual *Visual *Visual *Visual *Visual *Visual *Visual *Visual *Visual *Visual	>50 >20 Imit/base NONE NONE NONE NONE NONE NONE NONE NONE	2092 current 12 <1 1 current NONE NONE NONE NONE NONE NONE NONE NONE NONE NONE	 history1 history1 -	history2




OIL ANALYSIS REPORT

FLUID PROPERTIES method limit/base

current

history1

history2



	Visc @ 40°C	cSt	ASTM D445		33.4		
	SAMPLE IMA	GES	method	limit/base	current	history1	history2
23	Color				no image	no image	no image
Nov28/23	Bottom				no image	no image	no image
	GRAPHS						
	Ferrous Alloys			-			
	20 inn 18 chromium 16 12 12 - 10 8 6 -						
	Non-ferrous Meta	als		Nov28/23			
Ę	9 - copper 8 - lead 7 - 6						
	3			Nov28/23			
1	Viscosity @ 40°C						
cSt (40-c)	80						
	50			Nov28/23			
ATTIGETE L2367 Sample No. Lab Number Unique Number Test Package	: WearCheck USA - : GFL0102550 : 06027254 : 10777045 : FLEET	Received Diagnos Diagnos	d : 06 D ed : 08 D tician : Don	y, NC 27513 ec 2023 ec 2023 Baldridge	3 GFL Er	Ha Contact: BRY	State Route 29 arrisonville, M US 6470 AN SWANSO
ntificate 12367 Test Package o discuss this sample report, co Denotes test methods that are						AN SWANS	

Contact/Location: BRYAN SWANSON - GFL837