

OIL ANALYSIS REPORT

Sample Rating Trend







Machine Id **T330** Component **Rear Differential** Fluid **BELRAY Turbine Oil 150 (--- QTS)**

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

The condition of the oil is acceptable for the time in service.

| SAMPLE INFOR | MATION | method | limit/base | current | history1 | history2 |
|------------------|--------|-------------|------------|-------------|-----------|------------------|
| Sample Number | | Client Info | | PCA0104195 | | |
| Sample Date | | Client Info | | 02 Dec 2023 | | |
| Machine Age | mls | Client Info | | 25321 | | |
| Oil Age | mls | Client Info | | 0 | | |
| Oil Changed | | Client Info | | Not Changd | | |
| Sample Status | | | | NORMAL | | |
| CONTAMINAT | ION | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >.2 | NEG | | |
| WEAR METAL | S | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >500 | 67 | | |
| Chromium | ppm | ASTM D5185m | >10 | <1 | | |
| Nickel | ppm | ASTM D5185m | >10 | <1 | | |
| Titanium | ppm | ASTM D5185m | | 0 | | |
| Silver | ppm | ASTM D5185m | | 0 | | |
| Aluminum | ppm | ASTM D5185m | >25 | <1 | | |
| Lead | ppm | ASTM D5185m | >25 | 0 | | |
| Copper | ppm | ASTM D5185m | >100 | 1 | | |
| Tin | ppm | ASTM D5185m | >10 | 0 | | |
| Vanadium | ppm | ASTM D5185m | | 0 | | |
| Cadmium | ppm | ASTM D5185m | | 0 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 72 | | |
| Barium | ppm | ASTM D5185m | | 0 | | |
| Molybdenum | ppm | ASTM D5185m | | 0 | | |
| Manganese | ppm | ASTM D5185m | | 6 | | |
| Magnesium | ppm | ASTM D5185m | | 192 | | |
| Calcium | ppm | ASTM D5185m | | 8 | | |
| Phosphorus | ppm | ASTM D5185m | | 1772 | | |
| Zinc | ppm | ASTM D5185m | | 2 | | |
| Sulfur | ppm | ASTM D5185m | | 24714 | | |
| CONTAMINAN | NTS | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >75 | 15 | | |
| Sodium | ppm | ASTM D5185m | | 6 | | |
| Potassium | ppm | ASTM D5185m | >20 | 2 | | |
| VISUAL | | method | limit/base | current | history1 | history2 |
| White Metal | scalar | *Visual | NONE | NONE | | |
| Yellow Metal | scalar | *Visual | NONE | NONE | | |
| Precipitate | scalar | *Visual | NONE | NONE | | |
| Silt | scalar | *Visual | NONE | NONE | | |
| Debris | scalar | *Visual | NONE | NONE | | |
| Sand/Dirt | scalar | *Visual | NONE | NONE | | |
| Appearance | scalar | *Visual | NORML | NORML | | |
| Odor | scalar | *Visual | NORML | NORML | | |
| Emulsified Water | scalar | *Visual | >.2 | NEG | | |
| Free Water | scalar | *Visual | | NEG | | |
| 5:15:08) Rev: 1 | | | | | Submitted | By: Paul Riddick |



OIL ANALYSIS REPORT



| C | FLUID PROP | PERTIES | method | limit/base | current | history1 | history2 |
|---|--|--|---|--|----------|------------------------|--|
| | Visc @ 40°C | cSt | ASTM D445 | 142.2 | 98.7 | | |
| | SAMPLE IMA | AGES | method | limit/base | current | history1 | history2 |
| 23 | Color | | | | no image | no image | no image |
| Dec2/23 | Bottom | | | | no image | no image | no image |
| | GRAPHS | | | | | | |
| ud 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | Non-ferrous Met Non-ferrous Met Non-ferrous Met Non-ferrous Met Viscosity @ 40°0 Abnomal Base | | | Dec2/23 Dec2/23 | | | |
| | 120 Abnormal | | | | | | |
| | 90 | | | | | | |
| | Dec2/23 | | | Dec2/23 - | | | |
| | : WearCheck USA : PCA0104195 : 06028221 : 10778012 : FLEET ontact Customer Se e outside of the ISO | Received Diagnose Diagnosti rvice at 1-80 17025 scop | : 07 d : 10 cian : Dou 00-237-1369 de of accrea | ry, NC 2751: Dec 2023 Dec 2023 Ig Bogart 9. Vitation. | | Contact: G gedwards | SERVICE DIVISION NDENCE BLVD COLUMBIA, SC US 29210 eorge Edwards @nwwhite.com T: F: |