




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Area  
**166**  
Machine Id  
**414062**  
Component  
**1 Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

Metal levels are typical for a new component breaking in.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0100235</b>	GFL0100231	GFL0100234
Sample Date	Client Info		<b>05 Dec 2023</b>	15 Nov 2023	08 Nov 2023
Machine Age	hrs	Client Info	<b>745</b>	10133	10133
Oil Age	hrs	Client Info	<b>150</b>	613	600
Oil Changed	Client Info		<b>Not Changed</b>	Changed	Not Changed
Sample Status			<b>NORMAL</b>	ABNORMAL	ABNORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	<b>4</b>	26	28
Chromium	ppm	ASTM D5185m >20	<b>0</b>	<1	<1
Nickel	ppm	ASTM D5185m >5	<b>0</b>	<1	1
Titanium	ppm	ASTM D5185m >2	<b>0</b>	<1	<1
Silver	ppm	ASTM D5185m >2	<b>0</b>	1	2
Aluminum	ppm	ASTM D5185m >20	<b>2</b>	▲ 14	▲ 13
Lead	ppm	ASTM D5185m >40	<b>0</b>	<1	<1
Copper	ppm	ASTM D5185m >330	<b>26</b>	195	186
Tin	ppm	ASTM D5185m >15	<b>0</b>	3	3
Vanadium	ppm	ASTM D5185m	<b>0</b>	<1	<1
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	<1

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>12</b>	175	199
Barium	ppm	ASTM D5185m 0	<b>0</b>	<1	1
Molybdenum	ppm	ASTM D5185m 60	<b>60</b>	107	111
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	4	4
Magnesium	ppm	ASTM D5185m 1010	<b>962</b>	765	731
Calcium	ppm	ASTM D5185m 1070	<b>1078</b>	1317	1322
Phosphorus	ppm	ASTM D5185m 1150	<b>983</b>	678	747
Zinc	ppm	ASTM D5185m 1270	<b>1221</b>	872	853
Sulfur	ppm	ASTM D5185m 2060	<b>3152</b>	2291	2376

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>7</b>	▲ 54	▲ 60
Sodium	ppm	ASTM D5185m	<b>2</b>	2	<1
Potassium	ppm	ASTM D5185m >20	<b>5</b>	35	38

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	<b>0.1</b>	0.2	0.2
Nitration	Abs/cm	*ASTM D7624 >20	<b>5.3</b>	8.8	8.2
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>18.4</b>	23.8	24.1

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>14.3</b>	21.0	20.9
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>9.0</b>	8.5	8.5







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.7</b>	▲ 10.4	▲ 10.4

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0100235 **Received** : 11 Dec 2023  
**Lab Number** : **06030194** **Diagnosed** : 12 Dec 2023  
**Unique Number** : 10779985 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 166 - Phenix City**  
 18 Old Brickyard Rd  
 Phenix City, AL  
 US 36869  
 Contact: EDWARD CASHMAN  
 ecashman@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)