

OIL ANALYSIS REPORT

Sample Rating Trend

DEGRADATION



Component

Natural Gas Engine

CITGO PACEMAKER GAS ENGINE OIL 1015 15W40 (--- GAL)

DIAGNOSIS

Recommendation

We advise an early resample to confirm this situation. Please confirm the component type with your next sample.

Wear

All component wear rates are normal.

Contamination

Fuel content negligible. There is no indication of any contamination in the oil.

Fluid Condition

The oil viscosity is lower than normal. This plus the additive levels indicates the addition of a different brand, or type of oil. The BN level is low. Confirm oil type. The AN level is acceptable for this fluid.

5 15W40 (GA	AL)			Dec2023		
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0111957		
Sample Date		Client Info		04 Dec 2023		
Machine Age	hrs	Client Info		140489		
Oil Age	hrs	Client Info		329		
Oil Changed		Client Info		N/A		
Sample Status				ATTENTION		
CONTAMINAT	ION	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METAL	.S	method	limit/base	current	history1	history2
ron	ppm	ASTM D5185m	>50	<1		
Chromium	ppm	ASTM D5185m	>4	0		
Nickel	ppm	ASTM D5185m	>2	0		
Fitanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m	>3	0		
Aluminum	ppm	ASTM D5185m	>9	0		
ead	ppm	ASTM D5185m	>30	0		
Copper	ppm	ASTM D5185m	>35	<1		
Γin	ppm	ASTM D5185m	>4	2		
/anadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Nolybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		1		
Calcium	ppm	ASTM D5185m		1 3		
Phosphorus	ppm	ASTM D5185m		636		
Zinc	ppm	ASTM D5185m		▲ 393		
Sulfur	ppm	ASTM D5185m		1953		
CONTAMINAN	ITS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>+100	<1		
Sodium	ppm	ASTM D5185m		0		
Potassium	ppm	ASTM D5185m	>20	<1		
Fuel	%	ASTM D3524	>4.0	0.0		
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844		0		
Nitration	Abs/cm	*ASTM D7624	>20	2.2		
Sulfation	Abs/.1mm	*ASTM D7415	>30	11.6		
FLUID DEGRA		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	5.8		
Acid Number (AN)	mg KOH/g	ASTM D8045		1.07		
Base Number (BN)	mg KOH/g	ASTM D2896		▲ 0.50		
	y 1.01.19					



OIL ANALYSIS REPORT

