


# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**2026867**  
 Component  
**2 Differential**  
 Fluid  
**GEAR OIL SAE 80W90 (--- QTS)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>PCA0103345</b>	PCA0099769	PCA0095202
Sample Date	Client Info			<b>06 Aug 2023</b>	30 May 2023	27 Mar 2023
Machine Age	mls	Client Info		<b>336391</b>	311808	291746
Oil Age	mls	Client Info		<b>336391</b>	311808	291746
Oil Changed	Client Info			<b>Not Changed</b>	Not Changed	Not Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Water	WC Method		>.2	<b>NEG</b>	NEG	NEG


WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>500	<b>207</b>	205	195
Chromium	ppm	ASTM D5185m	>10	<b>2</b>	2	2
Nickel	ppm	ASTM D5185m	>10	<b>5</b>	5	6
Titanium	ppm	ASTM D5185m		<b>0</b>	0	0
Silver	ppm	ASTM D5185m		<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>25	<b>2</b>	2	3
Lead	ppm	ASTM D5185m	>25	<b>2</b>	0	0
Copper	ppm	ASTM D5185m	>100	<b>6</b>	5	3
Tin	ppm	ASTM D5185m	>10	<b>0</b>	0	1
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	0
Cadmium	ppm	ASTM D5185m		<b>0</b>	0	0

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	400	<b>250</b>	249	242
Barium	ppm	ASTM D5185m	200	<b>0</b>	0	1
Molybdenum	ppm	ASTM D5185m	12	<b>0</b>	0	<1
Manganese	ppm	ASTM D5185m		<b>10</b>	10	11
Magnesium	ppm	ASTM D5185m	12	<b>0</b>	0	4
Calcium	ppm	ASTM D5185m	150	<b>0</b>	0	7
Phosphorus	ppm	ASTM D5185m	1650	<b>1302</b>	1322	1385
Zinc	ppm	ASTM D5185m	125	<b>0</b>	0	12
Sulfur	ppm	ASTM D5185m	22500	<b>24655</b>	25426	28842

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>75	<b>35</b>	27	26
Sodium	ppm	ASTM D5185m	>170	<b>6</b>	6	6
Potassium	ppm	ASTM D5185m	>20	<b>10</b>	0	3

VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	MODER
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Precipitate	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Silt	scalar	*Visual	NONE	<b>LIGHT</b>	LIGHT	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>.2	<b>NEG</b>	NEG	NEG
Free Water	scalar	*Visual		<b>NEG</b>	NEG	NEG

# OIL ANALYSIS REPORT






### FLUID PROPERTIES

method	limit/base	current	history1	history2
Visc @ 40°C	cSt ASTM D445	143	<b>103</b>	103

### SAMPLE IMAGES

method	limit/base	current	history1	history2
Color			no image	no image
Bottom			no image	no image

### GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0103345 **Received** : 11 Dec 2023  
**Lab Number** : **06032006** **Diagnosed** : 14 Dec 2023  
**Unique Number** : 10781797 **Diagnostician** : Sean Felton  
**Test Package** : FLEET

**PERDUE FARMS - GEORGETOWN**  
 20621 SAVANAH RD  
 GEORGETOWN, DE  
 US 19947  
 Contact: ROBERT LOCKWOOD  
 Robert.Lockwood@Perdue.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: