




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**914058**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0105594</b>	GFL0101597	GFL0101521
Sample Date	Client Info		<b>09 Dec 2023</b>	17 Nov 2023	15 Nov 2023
Machine Age	hrs	Client Info	<b>10107</b>	10107	593
Oil Age	hrs	Client Info	<b>780</b>	548	548
Oil Changed	Client Info		<b>Not Chngd</b>	Changed	N/A
Sample Status			<b>NORMAL</b>	ABNORMAL	ATTENTION

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	<b>8</b>	42	37
Chromium	ppm	ASTM D5185m >20	<b>&lt;1</b>	1	1
Nickel	ppm	ASTM D5185m >5	<b>&lt;1</b>	4	3
Titanium	ppm	ASTM D5185m >2	<b>0</b>	<1	<1
Silver	ppm	ASTM D5185m >2	<b>&lt;1</b>	<1	<1
Aluminum	ppm	ASTM D5185m >20	<b>2</b>	5	5
Lead	ppm	ASTM D5185m >40	<b>0</b>	<1	2
Copper	ppm	ASTM D5185m >330	<b>36</b>	318	266
Tin	ppm	ASTM D5185m >15	<b>&lt;1</b>	3	2
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	<1
Cadmium	ppm	ASTM D5185m	<b>0</b>	<1	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>13</b>	192	154
Barium	ppm	ASTM D5185m 0	<b>0</b>	10	0
Molybdenum	ppm	ASTM D5185m 60	<b>60</b>	114	99
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	4	4
Magnesium	ppm	ASTM D5185m 1010	<b>938</b>	719	699
Calcium	ppm	ASTM D5185m 1070	<b>1094</b>	1333	1291
Phosphorus	ppm	ASTM D5185m 1150	<b>1057</b>	722	680
Zinc	ppm	ASTM D5185m 1270	<b>1264</b>	868	854
Sulfur	ppm	ASTM D5185m 2060	<b>3211</b>	2374	1951

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>9</b>	▲ 58	52
Sodium	ppm	ASTM D5185m	<b>26</b>	<1	4
Potassium	ppm	ASTM D5185m >20	<b>1</b>	8	5

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	<b>0.2</b>	0.6	0.5
Nitration	Abs/cm	*ASTM D7624 >20	<b>5.9</b>	9.8	9.4
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>18.8</b>	23.7	23.6

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>14.5</b>	21.9	21.3
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>8.6</b>	7.8	8.0







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	13.7	▲ 10.7

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0105594 **Received** : 12 Dec 2023  
**Lab Number** : 06032240 **Diagnosed** : 13 Dec 2023  
**Unique Number** : 10782031 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 415 - Michigan East**  
 6200 Elmridge  
 Sterling Heights, MI  
 US 48313  
 Contact: Frank Wolak  
 fwolak@gflenv.com  
 T: (586)825-9514  
 F:

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)