




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**413000**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (--- LTR)**



## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0078627</b>	GFL0078626	GFL0078653
Sample Date	Client Info		<b>04 Dec 2023</b>	04 Dec 2023	20 Sep 2023
Machine Age	hrs	Client Info	<b>2700</b>	950	2118
Oil Age	hrs	Client Info	<b>0</b>	0	460
Oil Changed	Client Info		<b>Changed</b>	N/A	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	<b>13</b>	17	8
Chromium	ppm	ASTM D5185m >20	<b>1</b>	<1	<1
Nickel	ppm	ASTM D5185m >5	<b>3</b>	3	0
Titanium	ppm	ASTM D5185m >2	<b>&lt;1</b>	<1	0
Silver	ppm	ASTM D5185m >2	<b>0</b>	1	<1
Aluminum	ppm	ASTM D5185m >20	<b>4</b>	4	2
Lead	ppm	ASTM D5185m >40	<b>&lt;1</b>	<1	0
Copper	ppm	ASTM D5185m >330	<b>10</b>	293	16
Tin	ppm	ASTM D5185m >15	<b>1</b>	2	1
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>&lt;1</b>	<1	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>3</b>	11	8
Barium	ppm	ASTM D5185m 0	<b>11</b>	11	0
Molybdenum	ppm	ASTM D5185m 60	<b>62</b>	68	66
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	1	<1
Magnesium	ppm	ASTM D5185m 1010	<b>938</b>	906	978
Calcium	ppm	ASTM D5185m 1070	<b>1053</b>	1080	1147
Phosphorus	ppm	ASTM D5185m 1150	<b>960</b>	932	1065
Zinc	ppm	ASTM D5185m 1270	<b>1212</b>	1157	1284
Sulfur	ppm	ASTM D5185m 2060	<b>3357</b>	3143	3710

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>6</b>	8	5
Sodium	ppm	ASTM D5185m	<b>2</b>	0	6
Potassium	ppm	ASTM D5185m >20	<b>9</b>	11	5

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	<b>0.4</b>	0.2	0.3
Nitration	Abs/cm	*ASTM D7624 >20	<b>9.1</b>	8.0	7.0
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>20.5</b>	19.9	18.7

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>17.5</b>	15.9	14.5
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>6.9</b>	7.9	7.8







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.6</b>	13.3	13.6

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0078627 **Received** : 12 Dec 2023  
**Lab Number** : **06032666** **Diagnosed** : 13 Dec 2023  
**Unique Number** : 10782457 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 152 - Jacksonville**  
 7580 PHILIPS HWY  
 Jacksonville, FL  
 US 32256  
 Contact: GRANVILLE CARROLL  
 gcarroll@gflenv.com  
 T: 1(904)252-6815  
 F:

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)