


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
JOHN DEERE E-CAB OT-98 (S/N 23562)

Component
Diesel Engine

Fluid
DIESEL ENGINE OIL SAE 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

Metal levels are typical for a new component breaking in.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	PCA0107014	PCA0107044	---
Sample Date	Client Info	30 Nov 2023	20 Oct 2023	---
Machine Age	hrs	819	571	---
Oil Age	hrs	250	250	---
Oil Changed	Client Info	Changed	Changed	---
Sample Status		NORMAL	NORMAL	---

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >2.1	<1.0	<1.0	---
Water	WC Method >0.21	NEG	NEG	---
Glycol	WC Method	NEG	NEG	---

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >51	6	11	---
Chromium	ppm ASTM D5185m >11	0	0	---
Nickel	ppm ASTM D5185m >5	0	0	---
Titanium	ppm ASTM D5185m	0	0	---
Silver	ppm ASTM D5185m >3	0	0	---
Aluminum	ppm ASTM D5185m >31	1	2	---
Lead	ppm ASTM D5185m >26	<1	3	---
Copper	ppm ASTM D5185m >26	<1	12	---
Tin	ppm ASTM D5185m >4	<1	<1	---
Vanadium	ppm ASTM D5185m	0	0	---
Cadmium	ppm ASTM D5185m	0	0	---

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 250	4	12	---
Barium	ppm ASTM D5185m 10	0	0	---
Molybdenum	ppm ASTM D5185m 100	58	63	---
Manganese	ppm ASTM D5185m	<1	<1	---
Magnesium	ppm ASTM D5185m 450	961	957	---
Calcium	ppm ASTM D5185m 3000	1081	1199	---
Phosphorus	ppm ASTM D5185m 1150	1060	964	---
Zinc	ppm ASTM D5185m 1350	1323	1319	---
Sulfur	ppm ASTM D5185m 4250	3226	2951	---

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >22	2	3	---
Sodium	ppm ASTM D5185m >158	<1	2	---
Potassium	ppm ASTM D5185m >20	0	1	---



INFRA-RED

method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	0.1	0.1	---
Nitration	Abs/cm *ASTM D7624 >20	5.6	7.0	---
Sulfation	Abs/.1mm *ASTM D7415 >30	18.0	18.7	---

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	14.1	15.1	---
Base Number (BN)	mg KOH/g ASTM D2896 8.5	10.59	7.75	---









OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.21	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	14.4	14.0	13.3	---

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0107014 **Received** : 14 Dec 2023
Lab Number : **06034756** **Diagnosed** : 18 Dec 2023
Unique Number : 10789985 **Diagnostician** : Wes Davis
Test Package : MOB 2

TRINITAS FARMING
 45499 W PANOCHE RD
 FIREBAUGH, CA
 US 93622

Contact: SPENCER COOPER
 spencer.cooper@trinitasfarming.com

T: (209)493-2999

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)