


# **OIL ANALYSIS REPORT**



**WEAR** 



738208

Component **Diesel Engine** 

PETRO CANADA DURON SHP 10W30 (--- G

# **DIAGNOSIS**

## Recommendation

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

#### Wear

Cylinder, crank, or cam shaft wear is indicated. All other component wear rates are normal.

#### Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. No other contaminants were detected in the oil.

## **Fluid Condition**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

iAL)			0ct2023	Nov <sup>2</sup> 023		
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number	1011	Client Info		PCA0112231	PCA0108359	
•		Client Info		30 Nov 2023	17 Oct 2023	
Sample Date	mla	Client Info		180929	164834	
Machine Age	mls	Client Info			164834	
Oil Age	mls	Client Info		70000 Channed	Not Changd	
Oil Changed		Ciletit IIIIO		Changed ABNORMAL	ABNORMAL	
Sample Status	1011					
CONTAMINAT	ION	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0	<1.0	
Water		WC Method	>0.2	NEG	NEG	
Glycol		WC Method		NEG	NEG	
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	<b>152</b>	<u>▲</u> 121	
Chromium	ppm	ASTM D5185m	>20	8	7	
Nickel	ppm	ASTM D5185m	>4	2	<1	
Titanium	ppm	ASTM D5185m		5	4	
Silver	ppm	ASTM D5185m	>3	0	0	
Aluminum	ppm	ASTM D5185m	>20	138	126	
Lead	ppm	ASTM D5185m	>40	<1	1	
Copper	ppm	ASTM D5185m	>330	189	167	
Tin	ppm	ASTM D5185m	>15	5	4	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		<1	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	4	4	
Barium	ppm	ASTM D5185m	0	12	0	
Molybdenum	ppm	ASTM D5185m	50	57	54	
Manganese	ppm	ASTM D5185m	0	3	2	
Magnesium	ppm	ASTM D5185m	950	850	813	
Calcium	ppm	ASTM D5185m	1050	1442	1357	
Phosphorus	ppm	ASTM D5185m	995	963	852	
Zinc	ppm	ASTM D5185m	1180	1250	1239	
Sulfur	ppm	ASTM D5185m	2600	2294	1900	
CONTAMINAN	ITS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	13	11	
Sodium	ppm	ASTM D5185m		2	6	
Potassium	ppm	ASTM D5185m	>20	345	300	
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	2.8	2.5	
Nitration	Abs/cm	*ASTM D7624	>20	16.4	14.8	
Sulfation	Abs/.1mm	*ASTM D7415	>30	31.5	29.1	
FLUID DEGRA	OATION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	31.0	27.4	
Base Number (BN)	mg KOH/g	ASTM D2896		3.2	4.3	
(=/•)	39					



# **OIL ANALYSIS REPORT**







Certificate L2367

Lab Number **Unique Number** 

: 06035831 : 10791060 Test Package : MOB 1 ( Additional Tests: TBN )

Diagnosed Diagnostician : Don Baldridge

: 19 Dec 2023

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) PHILADELPHIA, PA US 19116

Contact: ROSTY VITER rviter@millertransgroup.com T: (215)552-9832

Contact/Location: ROSTY VITER - MILPHINE

F: (215)552-9892