

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id 612494

Component Diesel Engine

Fluid PETRO CANADA DURON SHP 10W30 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.


GAL)			Jul2023	Dec2023		
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0112282	PCA0100774	
Sample Date		Client Info		12 Dec 2023	10 Jul 2023	
Machine Age	mls	Client Info		117155	108896	
Oil Age	mls	Client Info		117155	108896	
Oil Changed		Client Info		Not Changd	Changed	
Sample Status				NORMAL	NORMAL	
CONTAMINAT	ION	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0	<1.0	
Water		WC Method	>0.2	NEG	NEG	
Glycol		WC Method		NEG	NEG	
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	13	44	
Chromium	ppm	ASTM D5185m	>20	3	6	
Nickel	ppm	ASTM D5185m	>4	<1	<1	
Titanium	ppm	ASTM D5185m		2	9	
Silver	ppm	ASTM D5185m	>3	0	0	
Aluminum	ppm	ASTM D5185m	>20	12	36	
Lead	ppm	ASTM D5185m	>40	0	<1	
Copper	ppm	ASTM D5185m		17	62	
Tin	ppm	ASTM D5185m	>15	1	3	
Vanadium	ppm	ASTM D5185m	210	<1	<1	
Cadmium	ppm	ASTM D5185m		<1	0	
ADDITIVES	ppm	method	limit/base	current	history1	history2
						-
Boron	ppm	ASTM D5185m	2	5	4	
Barium	ppm	ASTM D5185m	0	12	0	
Molybdenum	ppm	ASTM D5185m	50	57	54	
Manganese	ppm	ASTM D5185m		<1	1	
Magnesium	ppm	ASTM D5185m	950	919	858	
Calcium	ppm	ASTM D5185m	1050	1127	1348	
Phosphorus	ppm	ASTM D5185m	995	978	937	
Zinc	ppm	ASTM D5185m	1180	1232	1209	
Sulfur	ppm	ASTM D5185m	2600	3437	2990	
CONTAMINAN	IIS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	4	4	
Sodium	ppm	ASTM D5185m		4	5	
Potassium	ppm	ASTM D5185m	>20	21	71	
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.5	1.2	
Nitration	Abs/cm	*ASTM D7624	>20	6.5	10.9	
Sulfation	Abs/.1mm	*ASTM D7415	>30	18.9	23.7	
FLUID DEGRA	DATION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	13.9	19.6	
Base Number (BN)	mg KOH/g	ASTM D2896		8.6	5.7	



OIL ANALYSIS REPORT







Unique Number Test Package : MOB 1 (Additional Tests: TBN) Certificate L2367 To discuss this sample report, contact Customer Service at 1-800-237-1369. rviter@millertransgroup.com * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Laboratory

Sample No.

Lab Number

T: (215)552-9832

F: (215)552-9892