


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
2026835

Component
Diesel Engine

Fluid
PETRO CANADA DURON UHP 5W30 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0110964	PCA0104335	PCA0100369
Sample Date	Client Info		08 Nov 2023	23 Aug 2023	14 Jun 2023
Machine Age	mls	Client Info	347902	326015	305457
Oil Age	mls	Client Info	0	40070	29512
Oil Changed	Client Info		Not Chngd	Changed	Not Chngd
Sample Status			NORMAL	---	ABNORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	<1.0	▲ 6.8
Water	WC Method	>0.2	NEG	NEG	NEG
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	27	29	29
Chromium	ppm	ASTM D5185m >20	<1	<1	<1
Nickel	ppm	ASTM D5185m >4	<1	<1	0
Titanium	ppm	ASTM D5185m	<1	1	2
Silver	ppm	ASTM D5185m >3	0	0	0
Aluminum	ppm	ASTM D5185m >20	2	3	8
Lead	ppm	ASTM D5185m >40	1	2	2
Copper	ppm	ASTM D5185m >330	8	6	14
Tin	ppm	ASTM D5185m >15	1	1	1
Vanadium	ppm	ASTM D5185m	0	0	0
Cadmium	ppm	ASTM D5185m	<1	<1	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	0	0	81
Barium	ppm	ASTM D5185m 0	12	0	0
Molybdenum	ppm	ASTM D5185m 64	59	57	15
Manganese	ppm	ASTM D5185m 0	<1	<1	1
Magnesium	ppm	ASTM D5185m 1160	896	891	180
Calcium	ppm	ASTM D5185m 820	1029	1085	371
Phosphorus	ppm	ASTM D5185m 1160	977	974	504
Zinc	ppm	ASTM D5185m 1260	1189	1205	313
Sulfur	ppm	ASTM D5185m 3000	3029	3277	2393

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	4	4	12
Sodium	ppm	ASTM D5185m	0	3	43
Potassium	ppm	ASTM D5185m >20	4	3	▲ 54



INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	0.4	0.5	0.2
Nitration	Abs/cm	*ASTM D7624 >20	8.6	10.1	5.8
Sulfation	Abs/.1mm	*ASTM D7415 >30	19.3	21.0	53.3

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	15.4	16.7	64.2
Base Number (BN)	mg KOH/g	ASTM D2896 11.0	7.1	6.6	▲ 0.0





OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	11.9	10.8	11.1 ▲ 7

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0110964 **Recieved** : 15 Dec 2023
Lab Number : 06035842 **Diagnosed** : 16 Dec 2023
Unique Number : 10791071 **Diagnostician** : Wes Davis
Test Package : FLEET

PERDUE FARMS - GEORGETOWN
 20621 SAVANAH RD
 GEORGETOWN, DE
 US 19947
 Contact: ROBERT LOCKWOOD
 Robert.Lockwood@Perdue.com
 T:
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)