


# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**633727**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 10W30 (--- QTS)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>PCA0093369</b>	PCA0078779	---
Sample Date	Client Info			<b>08 Dec 2023</b>	05 Jan 2023	---
Machine Age	mls Client Info			<b>68374</b>	19956	---
Oil Age	mls Client Info			<b>0</b>	0	---
Oil Changed	Client Info			<b>Changed</b>	Not Changd	---
Sample Status				<b>NORMAL</b>	NORMAL	---

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<b>&lt;1.0</b>	<1.0	---
Water	WC Method	>0.2		<b>NEG</b>	NEG	---
Glycol	WC Method			<b>NEG</b>	NEG	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	<b>69</b>	55	---
Chromium	ppm	ASTM D5185m	>20	<b>2</b>	<1	---
Nickel	ppm	ASTM D5185m	>4	<b>&lt;1</b>	0	---
Titanium	ppm	ASTM D5185m		<b>1</b>	0	---
Silver	ppm	ASTM D5185m	>3	<b>&lt;1</b>	0	---
Aluminum	ppm	ASTM D5185m	>20	<b>29</b>	26	---
Lead	ppm	ASTM D5185m	>40	<b>&lt;1</b>	<1	---
Copper	ppm	ASTM D5185m	>330	<b>19</b>	44	---
Tin	ppm	ASTM D5185m	>15	<b>2</b>	2	---
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	---
Cadmium	ppm	ASTM D5185m		<b>&lt;1</b>	0	---



ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	<b>5</b>	24	---
Barium	ppm	ASTM D5185m	0	<b>13</b>	0	---
Molybdenum	ppm	ASTM D5185m	50	<b>71</b>	10	---
Manganese	ppm	ASTM D5185m	0	<b>2</b>	2	---
Magnesium	ppm	ASTM D5185m	950	<b>1021</b>	754	---
Calcium	ppm	ASTM D5185m	1050	<b>1362</b>	1428	---
Phosphorus	ppm	ASTM D5185m	995	<b>1109</b>	759	---
Zinc	ppm	ASTM D5185m	1180	<b>1392</b>	935	---
Sulfur	ppm	ASTM D5185m	2600	<b>2923</b>	2665	---

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<b>14</b>	13	---
Sodium	ppm	ASTM D5185m		<b>1</b>	4	---
Potassium	ppm	ASTM D5185m	>20	<b>70</b>	64	---

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	<b>0.6</b>	0.4	---
Nitration	Abs/cm	*ASTM D7624	>20	<b>13.7</b>	11.1	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>28.2</b>	24.1	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>27.3</b>	19.6	---
Base Number (BN)	mg KOH/g	ASTM D2896		<b>3.5</b>	5.3	---









# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	12.00	<b>12.2</b>	11.9	---

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0093369 **Recieved** : 15 Dec 2023  
**Lab Number** : 06036550 **Diagnosed** : 19 Dec 2023  
**Unique Number** : 10791779 **Diagnostician** : Sean Felton  
**Test Package** : MOB 1 ( Additional Tests: TBN )

**MILLER TRUCK LEASING #117**  
 2666 LEISCZS BRIDGE RD  
 LEESPORT, PA  
 US 19533  
 Contact: JAMEY RITZ  
 jritz@millertransgroup.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: