


# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**1926725**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 10W30 (35 QTS)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>PCA0107395</b>	PCA0101694	PCA0092286
Sample Date	Client Info		<b>04 Oct 2023</b>	16 Jul 2023	10 Feb 2023
Machine Age	mls	Client Info	<b>0</b>	321709	0
Oil Age	mls	Client Info	<b>20000</b>	321709	20000
Oil Changed	Client Info		<b>Not Changed</b>	Not Changed	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>6.0	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	<b>62</b>	48	60
Chromium	ppm	ASTM D5185m >20	<b>1</b>	<1	1
Nickel	ppm	ASTM D5185m >2	<b>&lt;1</b>	<1	<1
Titanium	ppm	ASTM D5185m	<b>3</b>	4	27
Silver	ppm	ASTM D5185m >2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >25	<b>6</b>	5	15
Lead	ppm	ASTM D5185m >40	<b>1</b>	2	2
Copper	ppm	ASTM D5185m >330	<b>9</b>	8	11
Tin	ppm	ASTM D5185m >15	<b>2</b>	1	1
Vanadium	ppm	ASTM D5185m	<b>&lt;1</b>	0	<1
Cadmium	ppm	ASTM D5185m	<b>&lt;1</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	<b>0</b>	0	3
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m 50	<b>55</b>	60	35
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	<1	1
Magnesium	ppm	ASTM D5185m 950	<b>893</b>	915	646
Calcium	ppm	ASTM D5185m 1050	<b>1066</b>	1190	1225
Phosphorus	ppm	ASTM D5185m 995	<b>1004</b>	1022	846
Zinc	ppm	ASTM D5185m 1180	<b>1220</b>	1260	1028
Sulfur	ppm	ASTM D5185m 2600	<b>2516</b>	2981	3018

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>6</b>	6	6
Sodium	ppm	ASTM D5185m	<b>25</b>	14	23
Potassium	ppm	ASTM D5185m >20	<b>9</b>	9	38



## INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>0.7</b>	0.5	0.8
Nitration	Abs/cm	*ASTM D7624 >20	<b>12.8</b>	10.8	13.1
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>25.8</b>	22.6	28.3

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>24.4</b>	19.6	25.3
Base Number (BN)	mg KOH/g	ASTM D2896	<b>3.7</b>	5.5	4.0





# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	12.00	<b>11.0</b>	11.0	10.9

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0107395 **Received** : 15 Dec 2023  
**Lab Number** : **06036625** **Diagnosed** : 21 Dec 2023  
**Unique Number** : 10791854 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**PERDUE FARMS - GEORGETOWN**  
 20621 SAVANAH RD  
 GEORGETOWN, DE  
 US 19947  
 Contact: ROBERT LOCKWOOD  
 Robert.Lockwood@Perdue.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: