


OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id
26508
 Component
Front Differential
 Fluid
PETRO CANADA TRAXON SYNTHETIC 75W90 (--- QTS)

DIAGNOSIS

Recommendation
 No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear
 All component wear rates are normal.

Contamination
 Elemental level of silicon (Si) above normal indicating ingress of seal material.

Fluid Condition
 The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0109382	PCA0100154	PCA0078856
Sample Date	Client Info		18 Oct 2023	13 Jun 2023	30 Jul 2022
Machine Age	mls	Client Info	0	530509	466136
Oil Age	mls	Client Info	0	530509	466136
Oil Changed	Client Info		Not Chngd	Not Chngd	Not Chngd
Sample Status			ABNORMAL	NORMAL	ABNORMAL

CONTAMINATION	method	limit/base	current	history1	history2
Water	WC Method	>.2	NEG	NEG	NEG



WEAR METALS	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >500	251	384	331
Chromium	ppm	ASTM D5185m >10	2	4	3
Nickel	ppm	ASTM D5185m >10	6	6	5
Titanium	ppm	ASTM D5185m	<1	<1	<1
Silver	ppm	ASTM D5185m	0	0	0
Aluminum	ppm	ASTM D5185m >25	3	6	8
Lead	ppm	ASTM D5185m >25	2	44	43
Copper	ppm	ASTM D5185m >100	8	84	81
Tin	ppm	ASTM D5185m >10	<1	8	8
Vanadium	ppm	ASTM D5185m	<1	0	0
Cadmium	ppm	ASTM D5185m	<1	0	0

ADDITIVES	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 328	230	123	109
Barium	ppm	ASTM D5185m 1	0	0	0
Molybdenum	ppm	ASTM D5185m	<1	<1	<1
Manganese	ppm	ASTM D5185m	6	11	10
Magnesium	ppm	ASTM D5185m 1	1	0	<1
Calcium	ppm	ASTM D5185m 7	9	7	10
Phosphorus	ppm	ASTM D5185m 1145	1455	1589	1494
Zinc	ppm	ASTM D5185m 3	0	122	109
Sulfur	ppm	ASTM D5185m 17909	27547	27945	25056

CONTAMINANTS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >75	▲ 95	59	50
Sodium	ppm	ASTM D5185m	7	11	11
Potassium	ppm	ASTM D5185m >20	6	5	2

VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual NONE	NONE	NONE	NONE
Silt	scalar	*Visual NONE	NONE	LIGHT	NONE
Debris	scalar	*Visual NONE	NONE	NONE	▲ MODER
Sand/Dirt	scalar	*Visual NONE	NONE	NONE	NONE
Appearance	scalar	*Visual NORML	NORML	NORML	NORML
Odor	scalar	*Visual NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual >.2	NEG	NEG	NEG
Free Water	scalar	*Visual	NEG	NEG	NEG

OIL ANALYSIS REPORT






FLUID PROPERTIES

method	limit/base	current	history1	history2	
Visc @ 40°C	cSt ASTM D445	99.6	95.2	92.2	92.0

SAMPLE IMAGES

method	limit/base	current	history1	history2	
Color			no image	no image	no image
Bottom			no image	no image	no image

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0109382
Lab Number : 06037103
Unique Number : 10792332
Test Package : FLEET

PERDUE FARMS - GEORGETOWN
 20621 SAVANAH RD
 GEORGETOWN, DE
 US 19947
 Contact: ROBERT LOCKWOOD
 Robert.Lockwood@Perdue.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: