


# **OIL ANALYSIS REPORT**

## Sample Rating Trend







# Machine Id **T295**

Component **Transmission (Auto)** 

**COGNIS EMGARD 2805 ATF (--- QTS)** 

## DIAGNOSIS

## Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

## Contamination

There is no indication of any contamination in the fluid.

## **Fluid Condition**

The condition of the fluid is acceptable for the time in service.

Nov2020 Apr2021 Aug2021 Jun2022 May2022 Oct0022 May2022 Occ0023								
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2		
Sample Number		Client Info		PCA0102224	PCA0092571	PCA0079579		
Sample Date		Client Info		18 Dec 2023	27 Mar 2023	27 Oct 2022		
Machine Age	mls	Client Info		249638	201188	176121		
Oil Age	mls	Client Info		248638	201188	100388		
Oil Changed		Client Info		Not Changd	N/A	Not Changd		
Sample Status				NORMAL	NORMAL	NORMAL		
CONTAMINAT	ION	method	limit/base	current	history1	history2		
Water		WC Method	>0.1	NEG	NEG	NEG		
WEAR METAL	_S	method	limit/base	current	history1	history2		
Iron	ppm	ASTM D5185m	>160	25	28	17		
Chromium	ppm	ASTM D5185m	>5	0	0	0		
Nickel	ppm	ASTM D5185m	>5	0	0	0		
Titanium	ppm	ASTM D5185m		0	0	0		
Silver	ppm	ASTM D5185m	>5	0	0	0		
Aluminum	ppm	ASTM D5185m	>50	9	13	6		
Lead	ppm	ASTM D5185m	>50	3	2	3		
Copper	ppm	ASTM D5185m	>225	23	20	12		
Tin	ppm	ASTM D5185m	>10	<1	1	<1		
Vanadium	ppm	ASTM D5185m		<1	0	0		
Cadmium	ppm	ASTM D5185m		0	0	0		
ADDITIVES		method	limit/base	current	history1	history2		
Boron	ppm	ASTM D5185m		80	61	80		
Barium	ppm	ASTM D5185m		0	0	0		
Molybdenum	ppm	ASTM D5185m		<1	0	0		
Manganese	ppm	ASTM D5185m		0	1	<1		
Magnesium	ppm	ASTM D5185m		0	2	0		
Calcium	ppm	ASTM D5185m		134	119	120		
Phosphorus	ppm	ASTM D5185m		182	202	220		
Zinc	ppm	ASTM D5185m		12	7	7		
Sulfur	ppm	ASTM D5185m		1592	1466	1957		
CONTAMINAN	ITS	method	limit/base	current	history1	history2		
Silicon	ppm	ASTM D5185m	>20	4	5	4		
Sodium	ppm	ASTM D5185m		<1	1	0		
Potassium	ppm	ASTM D5185m	>20	0	0	0		
VISUAL		method	limit/base	current	history1	history2		
White Metal	scalar	*Visual	NONE	NONE	NONE	VLITE		
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG		
		43 ()		NIEO	NIEG			


NEG

scalar \*Visual

NEG NEG





## **OIL ANALYSIS REPORT**




FLUID PROPI	ERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	38.9	31.6	30.2	32.1
SAMPLE IMA	GES	method	limit/base	current	history1	history2
Color				no image	no image	no image
Bottom				no image	no image	no image

## **GRAPHS**









Certificate L2367

Laboratory Sample No. Lab Number Unique Number : 10796123 Test Package : FLEET

: PCA0102224 : 06040894

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Recieved : 20 Dec 2023 Diagnosed : 22 Dec 2023 Diagnostician : Don Baldridge

NW WHITE & CO - COLUMBIA DIVISION 100 INDEPENDENCE BLVD

COLUMBIA, SC US 29210

Contact: GEORGE EDWARDS

gedwards@nwwhite.com

T: F:

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)