




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
357048-630220

Component
Gasoline Engine

Fluid
GASOLINE ENGINE OIL SAE 5W20 (--- Shots)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2	
Sample Number	Client Info	GFL0102576	GFL0080389	GFL0066741	
Sample Date	Client Info	19 Dec 2023	06 Sep 2023	06 Apr 2023	
Machine Age	mls	Client Info	297133	284344	269393
Oil Age	mls	Client Info	0	0	0
Oil Changed	Client Info	Not Changed	Changed	Changed	
Sample Status		NORMAL	NORMAL	NORMAL	

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >4.0	<1.0	<1.0	<1.0
Water	WC Method >0.2	NEG	NEG	NEG
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >150	4	3	2
Chromium	ppm ASTM D5185m >20	<1	<1	<1
Nickel	ppm ASTM D5185m >5	0	0	0
Titanium	ppm ASTM D5185m	<1	0	0
Silver	ppm ASTM D5185m >2	0	0	0
Aluminum	ppm ASTM D5185m >40	3	<1	0
Lead	ppm ASTM D5185m >50	0	0	0
Copper	ppm ASTM D5185m >155	3	0	<1
Tin	ppm ASTM D5185m >10	<1	<1	0
Vanadium	ppm ASTM D5185m	<1	0	0
Cadmium	ppm ASTM D5185m	<1	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 75	86	42	48
Barium	ppm ASTM D5185m 5	13	0	0
Molybdenum	ppm ASTM D5185m 100	122	70	70
Manganese	ppm ASTM D5185m	<1	<1	<1
Magnesium	ppm ASTM D5185m 12	427	437	363
Calcium	ppm ASTM D5185m 2100	1267	1084	1034
Phosphorus	ppm ASTM D5185m 650	722	644	581
Zinc	ppm ASTM D5185m 850	817	740	696
Sulfur	ppm ASTM D5185m 2500	2925	2413	1831

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >30	8	8	7
Sodium	ppm ASTM D5185m >50	3	<1	<1
Potassium	ppm ASTM D5185m >20	4	0	<1

INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844	0	0.1	0
Nitration	Abs/cm *ASTM D7624 >20	8.3	7.0	5.4
Sulfation	Abs/.1mm *ASTM D7415 >30	19.0	14.8	12.9

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	12.1	8.2	7.1
Base Number (BN)	mg KOH/g ASTM D2896	5.0	6.1	5.1







OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445 7.5	8.4	8.6	8.6

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0102576 **Received** : 21 Dec 2023
Lab Number : 06041855 **Diagnosed** : 22 Dec 2023
Unique Number : 10802463 **Diagnostician** : Don Baldrige
Test Package : FLEET

GFL Environmental - 892 - Pauls Valley Hauling
 405 East Airport Industrial Road
 Pauls Valley, OK
 US 73075
 Contact: Tony Graham
 tgraham2@wcamerica.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: