

# **OIL ANALYSIS REPORT**





#### Component Diesel Engine Fluid

PETRO CANADA DURON SHP 10W30 (--- QTS)

# DIAGNOSIS

## Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

#### Wear

Metal levels are typical for a new component breaking in.

## Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.


# Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

QTS)		Jul2022	Dec2022	Mar2023 Aug2023	Dec2023	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0115233	PCA0104301	PCA0095964
Sample Date		Client Info		15 Dec 2023	18 Aug 2023	31 Mar 2023
Machine Age	mls	Client Info		62882	48270	34922
Oil Age	mls	Client Info		0	0	0
Oil Changed		Client Info		N/A	Not Changd	Changed
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINATI	ON	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	56	38	75
Chromium	ppm	ASTM D5185m	>20	4	2	4
Nickel	ppm	ASTM D5185m	>4	<1	0	1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>3	<1	<1	0
Aluminum	ppm	ASTM D5185m	>20	57	47	112
Lead	ppm	ASTM D5185m	>40	0	0	2
Copper	ppm	ASTM D5185m	>330	210	388	217
Tin	ppm	ASTM D5185m	>15	3	4	9
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	13	18	29
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	50	52	51	42
Manganese	ppm	ASTM D5185m	0	2	2	4
Magnesium	ppm	ASTM D5185m	950	811	828	554
Calcium	ppm	ASTM D5185m	1050	1291	1310	1649
Phosphorus	ppm	ASTM D5185m	995	891	938	727
Zinc	ppm	ASTM D5185m	1180	1120	1165	890
Sulfur	ppm	ASTM D5185m	2600	2234	3330	2216
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	6	4	7
Sodium	ppm	ASTM D5185m		2	2	5
Potassium	ppm	ASTM D5185m	>20	131	94	244
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	1.1	0.7	0.9
Nitration	Abs/cm	*ASTM D7624	>20	10.1	8.3	10.4
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.0	19.9	23.4
FLUID DEGRAD	DATION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	18.4	15.8	21.9
Base Number (BN)	mg KOH/g	ASTM D2896		7.3	8.0	7.8



# **OIL ANALYSIS REPORT**





Certificate L2367

Laboratory

Sample No.

Contact/Location: MIKE LONGETTE - MILRUT