

OIL ANALYSIS REPORT

Sample Rating Trend





Component Transmission (Auto) Fluid COGNIS EMGARD 2805 ATF (36 hrs)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	/ ATION	method	limit/base	current	history1	history2	
Sample Number		Client Info		PCA0114669	PCA0095660	PCA0081222	
Sample Date		Client Info		12 Dec 2023	04 Apr 2023	03 Nov 2022	
Machine Age	mls	Client Info		393890	335932	301062	
Oil Age	mls	Client Info		75000	75000	75000	
Oil Changed		Client Info		Changed	Not Changd	Changed	
Sample Status				NORMAL	ABNORMAL	NORMAL	
CONTAMINATI	ON	method	limit/base	current	history1	history2	
Water		WC Method	>0.1	NEG	NEG	NEG	
WEAR METALS	S	method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m	>160	58	28	54	
Chromium	ppm	ASTM D5185m	>5	0	0	0	
Nickel	ppm	ASTM D5185m	>5	0	0	0	
Titanium	ppm	ASTM D5185m		0	0	0	
Silver	ppm	ASTM D5185m	>5	0	0	0	
Aluminum	ppm	ASTM D5185m	>50	17	8	15	
Lead	ppm	ASTM D5185m	>50	9	6	23	
Copper	ppm	ASTM D5185m	>225	44	20	36	
Tin	ppm	ASTM D5185m	>10	<1	<1	2	
Vanadium	ppm	ASTM D5185m		<1	0	0	
Cadmium	ppm	ASTM D5185m		0	0	0	
ADDITIVES		method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m		84	91	120	
Barium	ppm	ASTM D5185m		0	0	0	
Molybdenum	ppm	ASTM D5185m		0	0	<1	
Manganese	ppm	ASTM D5185m		<1	<1	<1	
Magnesium	ppm	ASTM D5185m		0	2	0	
Calcium	ppm	ASTM D5185m		110	113	123	
Phosphorus	ppm	ASTM D5185m		230	216	304	
Zinc	ppm	ASTM D5185m		19	0	8	
Sulfur	ppm	ASTM D5185m		1723	1471	1948	
CONTAMINAN	TS	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m	>20	4	3	4	
Sodium	ppm	ASTM D5185m		6	4	6	
Potassium	ppm	ASTM D5185m	>20	0	0	0	
VISUAL		method	limit/base	current	history1	history2	
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE	
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	NONE	A MODER	NONE	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	NORML	
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG	
Free Water	scalar	*Visual		NEG	NEG	NEG	
:40:11) Rev: 1					Submitted By: Paul Riddick		



OIL ANALYSIS REPORT



FLUID PROPE	RTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	38.9	30.7	31.6	31.6
SAMPLE IMAG	ES	method	limit/base	current	history1	history2
Color				no image	no image	no image
Bottom				no image	no image	no image



NW WHITE & CO - SPECIAL SERVICE DIVISION 100 INDEPENDENCE BLVD COLUMBIA, SC US 29210 Contact: George Edwards gedwards@nwwhite.com T: 06:2012) F:



Unique Number : 10803361 Diagnostician : Don Baldridge Certificate 12367 Test Package : FLEET To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

: PCA0114669

: 06042753

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

: WearCheck USA - 501 Madison Ave., Cary, NC 27513

: 21 Dec 2023

: 24 Dec 2023

Recieved

Diagnosed

Laboratory

Sample No.

Lab Number