




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**812024**

Component  
**Diesel Engine**

Fluid  
**DIESEL ENGINE OIL SAE 40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2	
Sample Number	Client Info	<b>GFL0098255</b>	GFL0098183	GFL0083912	
Sample Date	Client Info	<b>19 Dec 2023</b>	27 Nov 2023	13 Oct 2023	
Machine Age	hrs	Client Info	<b>4238</b>	4158	3833
Oil Age	hrs	Client Info	<b>4238</b>	4158	3833
Oil Changed	Client Info	<b>N/A</b>	N/A	N/A	
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL	

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	<b>3</b>	25	10
Chromium	ppm ASTM D5185m >20	<b>&lt;1</b>	1	<1
Nickel	ppm ASTM D5185m >4	<b>1</b>	5	2
Titanium	ppm ASTM D5185m	<b>0</b>	<1	0
Silver	ppm ASTM D5185m >3	<b>&lt;1</b>	0	0
Aluminum	ppm ASTM D5185m >20	<b>&lt;1</b>	2	0
Lead	ppm ASTM D5185m >40	<b>0</b>	<1	<1
Copper	ppm ASTM D5185m >330	<b>2</b>	4	3
Tin	ppm ASTM D5185m >15	<b>0</b>	1	<1
Vanadium	ppm ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm ASTM D5185m	<b>0</b>	<1	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 250	<b>15</b>	4	6
Barium	ppm ASTM D5185m 10	<b>&lt;1</b>	12	2
Molybdenum	ppm ASTM D5185m 100	<b>60</b>	62	59
Manganese	ppm ASTM D5185m	<b>&lt;1</b>	<1	<1
Magnesium	ppm ASTM D5185m 450	<b>938</b>	950	825
Calcium	ppm ASTM D5185m 3000	<b>1126</b>	1080	1023
Phosphorus	ppm ASTM D5185m 1150	<b>1114</b>	946	928
Zinc	ppm ASTM D5185m 1350	<b>1279</b>	1225	1078
Sulfur	ppm ASTM D5185m 4250	<b>3193</b>	2563	2660

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>3</b>	4	3
Sodium	ppm ASTM D5185m >216	<b>2</b>	0	0
Potassium	ppm ASTM D5185m >20	<b>0</b>	3	2

## INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>0.2</b>	0.9	0.5
Nitration	Abs/cm *ASTM D7624 >20	<b>5.7</b>	8.8	6.8
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>17.7</b>	21.0	18.6

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>13.3</b>	16.5	13.8
Base Number (BN)	mg KOH/g ASTM D2896 8.5	<b>8.7</b>	6.7	7.8







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	14.4	<b>14.0</b>	13.6	13.6

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0098255 **Received** : 22 Dec 2023  
**Lab Number** : 06043927 **Diagnosed** : 26 Dec 2023  
**Unique Number** : 10804535 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 652 - Fredericksburg Hauling**  
 10954 Houser Drive  
 Fredericksburg, VA  
 US 22408  
 Contact: WILLIAM MILO  
 wmilo@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)