




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**913076**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**



## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0105822</b>	GFL0101527	GFL0064010
Sample Date	Client Info		<b>27 Dec 2023</b>	16 Nov 2023	15 Dec 2022
Machine Age	hrs	Client Info	<b>3494</b>	3216	962
Oil Age	hrs	Client Info	<b>3216</b>	962	0
Oil Changed	Client Info		<b>Changed</b>	Changed	Changed
Sample Status			<b>NORMAL</b>	NORMAL	ATTENTION

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<b>&lt;1.0</b>	<1.0	0.4
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	<b>10</b>	6	65
Chromium	ppm	ASTM D5185m >20	<b>&lt;1</b>	<1	2
Nickel	ppm	ASTM D5185m >5	<b>2</b>	<1	12
Titanium	ppm	ASTM D5185m >2	<b>0</b>	<1	<1
Silver	ppm	ASTM D5185m >2	<b>0</b>	0	2
Aluminum	ppm	ASTM D5185m >20	<b>1</b>	2	6
Lead	ppm	ASTM D5185m >40	<b>&lt;1</b>	0	<1
Copper	ppm	ASTM D5185m >330	<b>2</b>	3	214
Tin	ppm	ASTM D5185m >15	<b>&lt;1</b>	<1	6
Vanadium	ppm	ASTM D5185m	<b>0</b>	<1	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>2</b>	1	130
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	<1
Molybdenum	ppm	ASTM D5185m 60	<b>57</b>	54	123
Manganese	ppm	ASTM D5185m 0	<b>0</b>	<1	6
Magnesium	ppm	ASTM D5185m 1010	<b>934</b>	892	731
Calcium	ppm	ASTM D5185m 1070	<b>1196</b>	1047	1545
Phosphorus	ppm	ASTM D5185m 1150	<b>1009</b>	966	750
Zinc	ppm	ASTM D5185m 1270	<b>1213</b>	1220	924
Sulfur	ppm	ASTM D5185m 2060	<b>2985</b>	2775	2693

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>3</b>	6	70
Sodium	ppm	ASTM D5185m	<b>1</b>	3	0
Potassium	ppm	ASTM D5185m >20	<b>0</b>	2	10

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	<b>0.7</b>	0.3	1.2
Nitration	Abs/cm	*ASTM D7624 >20	<b>7.9</b>	5.7	8.5
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>19.4</b>	18.5	22.2

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>15.2</b>	13.9	15.8
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>7.8</b>	8.6	11.4







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	13.7	14.0 ▲ 10.6

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0105822 **Received** : 28 Dec 2023  
**Lab Number** : 06046696 **Diagnosed** : 28 Dec 2023  
**Unique Number** : 10807304 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 415 - Michigan East**  
 6200 Elmridge  
 Sterling Heights, MI  
 US 48313  
 Contact: Frank Wolak  
 fwolak@gflenv.com  
 T: (586)825-9514  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)