


OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Area
(89951X) Walgreens - Tractor
Machine Id
[Walgreens - Tractor] 136A69013
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 10W30 (11 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

| SAMPLE INFORMATION | | method | limit/base | current | history1 | history2 |
|--------------------|-----------------|--------|------------|--------------------|-------------|----------|
| Sample Number | Client Info | | | PCA0105407 | PCA0105403 | --- |
| Sample Date | Client Info | | | 20 Dec 2023 | 15 Dec 2023 | --- |
| Machine Age | mls Client Info | | | 526211 | 524939 | --- |
| Oil Age | mls Client Info | | | 25000 | 28300 | --- |
| Oil Changed | Client Info | | | Not Chngd | Not Chngd | --- |
| Sample Status | | | | NORMAL | NORMAL | --- |

| CONTAMINATION | | method | limit/base | current | history1 | history2 |
|---------------|-----------|--------|------------|----------------|----------|----------|
| Fuel | WC Method | >5 | | <1.0 | <1.0 | --- |
| Water | WC Method | >0.2 | | NEG | NEG | --- |
| Glycol | WC Method | | | NEG | NEG | --- |

| WEAR METALS | | method | limit/base | current | history1 | history2 |
|-------------|-----|-------------|------------|--------------|----------|----------|
| Iron | ppm | ASTM D5185m | >80 | 15 | 14 | --- |
| Chromium | ppm | ASTM D5185m | >5 | 2 | 2 | --- |
| Nickel | ppm | ASTM D5185m | >2 | <1 | <1 | --- |
| Titanium | ppm | ASTM D5185m | | <1 | 0 | --- |
| Silver | ppm | ASTM D5185m | >3 | 0 | 0 | --- |
| Aluminum | ppm | ASTM D5185m | >30 | 12 | 9 | --- |
| Lead | ppm | ASTM D5185m | >30 | <1 | 0 | --- |
| Copper | ppm | ASTM D5185m | >150 | 6 | 6 | --- |
| Tin | ppm | ASTM D5185m | >5 | 2 | 1 | --- |
| Vanadium | ppm | ASTM D5185m | | 0 | <1 | --- |
| Cadmium | ppm | ASTM D5185m | | 0 | <1 | --- |



| ADDITIVES | | method | limit/base | current | history1 | history2 |
|------------|-----|-------------|------------|--------------|----------|----------|
| Boron | ppm | ASTM D5185m | 2 | 3 | 3 | --- |
| Barium | ppm | ASTM D5185m | 0 | 0 | 0 | --- |
| Molybdenum | ppm | ASTM D5185m | 50 | 63 | 62 | --- |
| Manganese | ppm | ASTM D5185m | 0 | <1 | <1 | --- |
| Magnesium | ppm | ASTM D5185m | 950 | 1053 | 977 | --- |
| Calcium | ppm | ASTM D5185m | 1050 | 1131 | 1073 | --- |
| Phosphorus | ppm | ASTM D5185m | 995 | 1093 | 1042 | --- |
| Zinc | ppm | ASTM D5185m | 1180 | 1314 | 1274 | --- |
| Sulfur | ppm | ASTM D5185m | 2600 | 2926 | 2794 | --- |

| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
|--------------|-----|-------------|------------|-----------|----------|----------|
| Silicon | ppm | ASTM D5185m | >20 | 10 | 10 | --- |
| Sodium | ppm | ASTM D5185m | | 1 | 2 | --- |
| Potassium | ppm | ASTM D5185m | >20 | 3 | 2 | --- |

| INFRA-RED | | method | limit/base | current | history1 | history2 |
|-----------|----------|-------------|------------|-------------|----------|----------|
| Soot % | % | *ASTM D7844 | >3 | 0.7 | 0.7 | --- |
| Nitration | Abs/cm | *ASTM D7624 | >20 | 8.7 | 8.5 | --- |
| Sulfation | Abs/.1mm | *ASTM D7415 | >30 | 21.6 | 21.4 | --- |

| FLUID DEGRADATION | | method | limit/base | current | history1 | history2 |
|-------------------|----------|-------------|------------|-------------|----------|----------|
| Oxidation | Abs/.1mm | *ASTM D7414 | >25 | 18.1 | 18.0 | --- |
| Base Number (BN) | mg KOH/g | ASTM D2896 | | 6.1 | 6.2 | --- |





OIL ANALYSIS REPORT



| VISUAL | method | limit/base | current | history1 | history2 |
|------------------|--------|------------|---------|----------|----------|
| White Metal | scalar | *Visual | NONE | NONE | --- |
| Yellow Metal | scalar | *Visual | NONE | NONE | --- |
| Precipitate | scalar | *Visual | NONE | NONE | --- |
| Silt | scalar | *Visual | NONE | NONE | --- |
| Debris | scalar | *Visual | NONE | NONE | --- |
| Sand/Dirt | scalar | *Visual | NONE | NONE | --- |
| Appearance | scalar | *Visual | NORML | NORML | --- |
| Odor | scalar | *Visual | NORML | NORML | --- |
| Emulsified Water | scalar | *Visual | >0.2 | NEG | --- |
| Free Water | scalar | *Visual | | NEG | --- |

| FLUID PROPERTIES | method | limit/base | current | history1 | history2 | |
|------------------|--------|------------|---------|-------------|----------|-----|
| Visc @ 100°C | cSt | ASTM D445 | 12.00 | 12.0 | 11.9 | --- |

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0105407 **Received** : 29 Dec 2023
Lab Number : **06047545** **Diagnosed** : 29 Dec 2023
Unique Number : 10808153 **Diagnostician** : Wes Davis
Test Package : FLEET

Transervice - Shop 1366 - Berkeley-Woodland
 2370 East Main Street
 Woodland, CA
 US 95776
 Contact: Gary Mann
 gmanna@transervice.com
 T: (530)666-7771
 F: (530)406-7971

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)