




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area
(Vin)
Machine Id
10503C Autocar ACX64
Component
Natural Gas Engine
Fluid
PETRO CANADA DURON GEO LD 15W40 (28 QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0103237	GFL0089345	GFL0056516
Sample Date	Client Info		29 Dec 2023	20 Jul 2023	11 Oct 2022
Machine Age	hrs	Client Info	8061	7241	5384
Oil Age	hrs	Client Info	0	0	951
Oil Changed	Client Info		Changed	Not Changd	Changed
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.1	NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >50	13	15	6
Chromium	ppm	ASTM D5185m >4	1	2	2
Nickel	ppm	ASTM D5185m >2	0	<1	0
Titanium	ppm	ASTM D5185m	0	<1	<1
Silver	ppm	ASTM D5185m >3	0	0	<1
Aluminum	ppm	ASTM D5185m >9	2	5	1
Lead	ppm	ASTM D5185m >30	0	0	2
Copper	ppm	ASTM D5185m >35	0	10	1
Tin	ppm	ASTM D5185m >4	0	<1	<1
Vanadium	ppm	ASTM D5185m	0	<1	<1
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 50	<1	15	30
Barium	ppm	ASTM D5185m 5	4	0	0
Molybdenum	ppm	ASTM D5185m 50	48	54	47
Manganese	ppm	ASTM D5185m 0	0	<1	1
Magnesium	ppm	ASTM D5185m 560	498	585	523
Calcium	ppm	ASTM D5185m 1510	1468	1707	1520
Phosphorus	ppm	ASTM D5185m 780	707	797	716
Zinc	ppm	ASTM D5185m 870	902	977	908
Sulfur	ppm	ASTM D5185m 2040	2529	2928	2683

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >+100	0	6	6
Sodium	ppm	ASTM D5185m	3	10	12
Potassium	ppm	ASTM D5185m >20	8	4	2

INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	0	0	0.1
Nitration	Abs/cm	*ASTM D7624 >20	11.1	10.1	8.1
Sulfation	Abs/.1mm	*ASTM D7415 >30	21.5	21.7	20.6

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	18.0	18.4	17.2
Base Number (BN)	mg KOH/g	ASTM D2896 10.2	3.8	5.8	8.8







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.1	14.4	14.7

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
 Sample No. : GFL0103237
 Lab Number : 06048562
 Unique Number : 10809170
 Test Package : FLEET
 Recieved : 02 Jan 2024
 Diagnosed : 03 Jan 2024
 Diagnostician : Wes Davis

GFL Environmental - 001 - Raleigh(CNG)
 3741 Conquest Drive
 Garner, NC
 US 27529
 Contact: Craig Johnson
 craig.johnson@gflenv.com
 T: (919)662-7100
 F: (919)662-7130

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)