


# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Area  
**(16094Z) Walgreens - Tractor**  
Machine Id  
**[Walgreens - Tractor] 136A63374**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 10W30 (11 GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>PCA0105456</b>	PCA0105437	PCA0105394
Sample Date	Client Info		<b>28 Dec 2023</b>	30 Oct 2023	08 Sep 2023
Machine Age	mls	Client Info	<b>155116</b>	119607	93307
Oil Age	mls	Client Info	<b>35509</b>	25000	24000
Oil Changed	Client Info		<b>Not Changed</b>	Changed	Not Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>2.0	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	<b>24</b>	36	22
Chromium	ppm	ASTM D5185m >20	<b>1</b>	2	2
Nickel	ppm	ASTM D5185m >4	<b>4</b>	<1	7
Titanium	ppm	ASTM D5185m	<b>0</b>	<1	0
Silver	ppm	ASTM D5185m >3	<b>0</b>	<1	<1
Aluminum	ppm	ASTM D5185m >20	<b>14</b>	14	10
Lead	ppm	ASTM D5185m >40	<b>0</b>	<1	0
Copper	ppm	ASTM D5185m >330	<b>6</b>	6	8
Tin	ppm	ASTM D5185m >15	<b>&lt;1</b>	1	1
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	<b>6</b>	3	12
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m 50	<b>59</b>	62	59
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	1	2
Magnesium	ppm	ASTM D5185m 950	<b>977</b>	872	891
Calcium	ppm	ASTM D5185m 1050	<b>1096</b>	1122	1185
Phosphorus	ppm	ASTM D5185m 995	<b>997</b>	946	1004
Zinc	ppm	ASTM D5185m 1180	<b>1332</b>	1193	1373
Sulfur	ppm	ASTM D5185m 2600	<b>2846</b>	2739	3585

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>6</b>	11	11
Sodium	ppm	ASTM D5185m	<b>1</b>	0	5
Potassium	ppm	ASTM D5185m >20	<b>33</b>	38	24



## INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>0.5</b>	0.5	0.3
Nitration	Abs/cm	*ASTM D7624 >20	<b>8.2</b>	8.9	7.0
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>20.0</b>	21.0	19.5

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>16.5</b>	17.7	16.0
Base Number (BN)	mg KOH/g	ASTM D2896	<b>7.4</b>	6.8	8.2





# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	12.00	<b>11.7</b>	11.6	11.5

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0105456 **Received** : 05 Jan 2024  
**Lab Number** : **06051783** **Diagnosed** : 05 Jan 2024  
**Unique Number** : 10817732 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**Transervice - Shop 1366 - Berkeley-Woodland**  
 2370 East Main Street  
 Woodland, CA  
 US 95776  
 Contact: Gary Mann  
 gmanna@transervice.com  
 T: (530)666-7771  
 F: (530)406-7971

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)