


OIL ANALYSIS REPORT

Sample Rating Trend



GLYCOL



Machine Id **921047-260381**

Component **Diesel Engine**

Fluid

PETRO CANADA DURON SHP 15W40 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

Sodium and/or potassium levels are high. Test for glycol is negative.


▲ Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.


GAL)		May2019 Jan2	023 Mar2023 Jun2023 Sep2	023 Oct2023 Nov2023 Nov2023 Doc2	023 Dec2023	
SAMPLE INFORM	1ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0102487	GFL0102436	GFL0098590
Sample Date		Client Info		28 Dec 2023	19 Dec 2023	28 Nov 2023
Machine Age	hrs	Client Info		6903	6851	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	N/A	N/A
Sample Status				ATTENTION		ATTENTION
CONTAMINATION	NC	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
WEAR METALS	5	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	15	14	13
Chromium	ppm	ASTM D5185m	>20	1	<1	<1
Nickel	ppm	ASTM D5185m	>4	0	<1	0
Titanium	ppm	ASTM D5185m		0	0	<1
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	4	5	4
Lead	ppm	ASTM D5185m	>40	<1	<1	0
Copper	ppm	ASTM D5185m	>330	2	2	2
Tin	ppm	ASTM D5185m	>15	<1	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	4	6	5
Barium	ppm	ASTM D5185m	0	0	0	6
Molybdenum	ppm	ASTM D5185m	60	61	65	67
Manganese	ppm	ASTM D5185m	0	<1	<1	0
Magnesium	ppm	ASTM D5185m	1010	913	990	911
Calcium	ppm	ASTM D5185m	1070	1032	1093	1100
Phosphorus	ppm	ASTM D5185m	1150	1038	1131	1005
Zinc	ppm	ASTM D5185m	1270	1181	1373	1194
Sulfur	ppm	ASTM D5185m	2060	2918	3300	3023
CONTAMINANT	ΓS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	6	7	8
Sodium	ppm	ASTM D5185m		154	149	1 52
Potassium	ppm	ASTM D5185m	>20	5	5	7
Glycol	%	*ASTM D2982		NEG	NEG	NEG
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.7	0.5	0.5
Nitration	Abs/cm	*ASTM D7624	>20	8.0	6.9	7.0
Sulfation	Abs/.1mm	*ASTM D7415		20.1	20.1	19.4
FLUID DEGRAD	ATION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	15.1	15.1	14.5
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	8.2	8.1	8.7
(2.1)	.5 9	J				



OIL ANALYSIS REPORT










VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	LIGHT	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROPERTIES		method				history2	
Visc @ 100°C	cSt	ASTM D445	15.4	13.9	13.8	13.9	

GRAPHS













Laboratory Sample No. Lab Number Unique Number

: GFL0102487 : 06053324 : 10819273

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Recieved

Diagnosed Diagnostician

: 09 Jan 2024 : Jonathan Hester

: 08 Jan 2024

Test Package : FLEET (Additional Tests: Glycol)

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

GFL Environmental - 837 - Harrison TS

22820 S State Route 291 Harrisonville, MO

US 64701 Contact: BRYAN SWANSON

bryanswanson@gflenv.com

T: F:

Contact/Location: BRYAN SWANSON - GFL837