




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**727154**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**



## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2	
Sample Number	Client Info	<b>GFL0108401</b>	GFL0084540	GFL0078771	
Sample Date	Client Info	<b>29 Dec 2023</b>	13 Jul 2023	13 Apr 2023	
Machine Age	hrs	Client Info	<b>1447</b>	689	10351
Oil Age	hrs	Client Info	<b>1447</b>	0	0
Oil Changed	Client Info	<b>Changed</b>	N/A	Changed	
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL	

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >120	<b>5</b>	9	9
Chromium	ppm ASTM D5185m >20	<b>&lt;1</b>	<1	<1
Nickel	ppm ASTM D5185m >5	<b>0</b>	0	0
Titanium	ppm ASTM D5185m >2	<b>0</b>	0	0
Silver	ppm ASTM D5185m >2	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >20	<b>&lt;1</b>	<1	<1
Lead	ppm ASTM D5185m >40	<b>1</b>	1	0
Copper	ppm ASTM D5185m >330	<b>7</b>	32	13
Tin	ppm ASTM D5185m >15	<b>1</b>	3	<1
Vanadium	ppm ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>&lt;1</b>	3	<1
Barium	ppm ASTM D5185m 0	<b>0</b>	0	1
Molybdenum	ppm ASTM D5185m 60	<b>56</b>	59	57
Manganese	ppm ASTM D5185m 0	<b>0</b>	<1	<1
Magnesium	ppm ASTM D5185m 1010	<b>943</b>	1016	895
Calcium	ppm ASTM D5185m 1070	<b>1019</b>	1085	984
Phosphorus	ppm ASTM D5185m 1150	<b>1077</b>	1070	947
Zinc	ppm ASTM D5185m 1270	<b>1201</b>	1326	1160
Sulfur	ppm ASTM D5185m 2060	<b>3124</b>	3917	3117

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>2</b>	3	2
Sodium	ppm ASTM D5185m	<b>&lt;1</b>	<1	<1
Potassium	ppm ASTM D5185m >20	<b>0</b>	<1	0

## INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >4	<b>0.6</b>	1.2	1.1
Nitration	Abs/cm *ASTM D7624 >20	<b>7.1</b>	6.7	6.6
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>19.1</b>	19.9	17.7

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>14.9</b>	13.5	12.9
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>8.9</b>	9.5	8.0







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.7</b>	13.5	13.2

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0108401 **Recieved** : 08 Jan 2024  
**Lab Number** : **06053614** **Diagnosed** : 09 Jan 2024  
**Unique Number** : 10819563 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 918 - Hartland HC**  
 630 E Industrial Drive  
 Hartland, WI  
 US 53029  
 Contact: David McCall  
 david.mccall@gflenv.com  
 T: (262)369-3069  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)