




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area
TALLASSEE
Machine Id
927049-162509
Component
Diesel Engine
Fluid
MOBIL DELVAC 1300 SUPER15W40 (--- LTR)



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0079718	GFL0092357	GFL0092426
Sample Date	Client Info	20 Dec 2023	04 Dec 2023	17 Oct 2023
Machine Age	hrs	17881	17771	318192
Oil Age	hrs	17881	17771	0
Oil Changed	Client Info	N/A	N/A	Changed
Sample Status		NORMAL	NORMAL	ABNORMAL

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >3.0	<1.0	<1.0	<1.0
Water	WC Method >0.2	NEG	NEG	NEG
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >120	15	13	49
Chromium	ppm ASTM D5185m >20	<1	0	<1
Nickel	ppm ASTM D5185m >5	3	2	2
Titanium	ppm ASTM D5185m >2	0	0	<1
Silver	ppm ASTM D5185m >2	0	0	0
Aluminum	ppm ASTM D5185m >20	6	5	▲ 17
Lead	ppm ASTM D5185m >40	0	0	2
Copper	ppm ASTM D5185m >330	<1	<1	3
Tin	ppm ASTM D5185m >15	0	<1	1
Vanadium	ppm ASTM D5185m	0	0	<1
Cadmium	ppm ASTM D5185m	0	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	20	10	12
Barium	ppm ASTM D5185m 0	0	0	0
Molybdenum	ppm ASTM D5185m 0	58	58	62
Manganese	ppm ASTM D5185m	0	<1	1
Magnesium	ppm ASTM D5185m 0	874	919	891
Calcium	ppm ASTM D5185m	1151	1011	1089
Phosphorus	ppm ASTM D5185m	972	1032	952
Zinc	ppm ASTM D5185m	1165	1259	1224
Sulfur	ppm ASTM D5185m	3182	3191	3104

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	8	10	▲ 31
Sodium	ppm ASTM D5185m	8	7	29
Potassium	ppm ASTM D5185m >20	3	2	7

INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >4	1	0.8	1.2
Nitration	Abs/cm *ASTM D7624 >20	7.2	6.8	9.7
Sulfation	Abs/.1mm *ASTM D7415 >30	19.7	18.7	21.6

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	14.7	13.7	15.5
Base Number (BN)	mg KOH/g ASTM D2896 9.4	9.0	8.7	7.8







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445 14	13.3	13.5	13.5

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0079718 **Recieved** : 10 Jan 2024
Lab Number : **06057296** **Diagnosed** : 11 Jan 2024
Unique Number : 10823245 **Diagnostician** : Wes Davis
Test Package : FLEET

GFL Environmental - 172 - Montgomery-Alexander City-Tallahassee
 Multiple Sites
 Montgomery, AL
 US 36108
 Contact: RICHARD HATFIELD
 rhatfield@gflenv.com

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)