

# **OIL ANALYSIS REPORT**

Sample Rating Trend



NORMAL



Machine Id
2702
Component
Diesel Engine

Fluid

## PETRO CANADA DURON SHP 15W40 (11 GAL)

# DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil


### **Fluid Condition**


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

ห <u>ลือา</u> 18 องสอิกายิ Jum2ิอาวา Feb2ิช2อ Jun2ิอาว Mav2ิช21 Jun2ิอาวา องสอิชว Mav2ิช23 Jan2ิอา						
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0072113	GFL0083651	GFL0074589
Sample Date		Client Info		04 Jan 2024	28 Sep 2023	12 Jul 2023
Machine Age	hrs	Client Info		16087	15398	14831
Oil Age	hrs	Client Info		600	567	150
Oil Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINAT	ION	method	limit/base	current	history1	history2
Fuel		WC Method	>3.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>165	23	12	10
Chromium	ppm	ASTM D5185m	>5	1	1	<1
Nickel	ppm	ASTM D5185m	>4	0	<1	<1
Titanium	ppm	ASTM D5185m	>2	<1	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>20	3	2	1
Lead	ppm	ASTM D5185m	>150	2	2	<1
Copper	ppm	ASTM D5185m	>90	3	8	3
Tin	ppm	ASTM D5185m	>5	<1	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	4	2	6
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	60	62	68	64
Manganese	ppm	ASTM D5185m	0	<1	<1	<1
Magnesium	ppm	ASTM D5185m	1010	896	954	849
Calcium	ppm	ASTM D5185m	1070	1005	1053	1058
Phosphorus	ppm	ASTM D5185m	1150	1026	1036	979
Zinc	ppm	ASTM D5185m	1270	1158	1280	1131
Sulfur	ppm	ASTM D5185m	2060	3102	3151	3003
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>35	7	6	5
Sodium	ppm	ASTM D5185m		2	4	1
Potassium	ppm	ASTM D5185m	>20	6	1	2
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>7.5	0.7	0.5	0.3
Nitration	Abs/cm	*ASTM D7624	>20	10.1	9.3	6.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	20.8	20.1	18.1
FLUID DEGRA	NOITAC	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	16.9	16.2	13.9
Base Number (BN)	mg KOH/g	<b>ASTM D2896</b>	9.8	6.7	7.2	8.3



## **OIL ANALYSIS REPORT**








VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
<b>Emulsified Water</b>	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROPE	ERTIES	method				history2
Visc @ 100°C	cSt	ASTM D445	15.4	12.9	13.0	13.4

### **GRAPHS**













Certificate L2367

Laboratory Sample No. Lab Number

: 06058649 : 10830031 **Unique Number** Test Package : FLEET

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : GFL0072113 Recieved : 11 Jan 2024 Diagnosed : 12 Jan 2024

Diagnostician : Wes Davis

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

GFL Environmental - 095 - Atlanta West

2699 Cochran Industrial Blvd Douglasville, GA US 30127-1332 Contact: Darrell Welch

darrell.welch@gflenv.com T: (800)207-6618