


# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Area  
**(16062Z) Walgreens - Tractor**  
 Machine Id  
**[Walgreens - Tractor] 136A61352**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 10W30 (11 GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>PCA0103631</b>	PCA0099942	PCA0092838
Sample Date	Client Info	<b>08 Jan 2024</b>	17 Aug 2023	06 Mar 2023
Machine Age	mls Client Info	<b>342378</b>	312906	255919
Oil Age	mls Client Info	<b>26318</b>	50000	50000
Oil Changed	Client Info	<b>Changed</b>	Changed	Changed
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >80	<b>21</b>	14	29
Chromium	ppm ASTM D5185m >5	<b>&lt;1</b>	<1	2
Nickel	ppm ASTM D5185m >2	<b>0</b>	0	0
Titanium	ppm ASTM D5185m	<b>0</b>	0	0
Silver	ppm ASTM D5185m >3	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >30	<b>8</b>	7	12
Lead	ppm ASTM D5185m >30	<b>0</b>	0	0
Copper	ppm ASTM D5185m >150	<b>4</b>	4	10
Tin	ppm ASTM D5185m >5	<b>0</b>	<1	<1
Vanadium	ppm ASTM D5185m	<b>0</b>	<1	0
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 2	<b>4</b>	<1	3
Barium	ppm ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm ASTM D5185m 50	<b>60</b>	64	59
Manganese	ppm ASTM D5185m 0	<b>0</b>	<1	<1
Magnesium	ppm ASTM D5185m 950	<b>1011</b>	952	872
Calcium	ppm ASTM D5185m 1050	<b>1178</b>	1153	1057
Phosphorus	ppm ASTM D5185m 995	<b>1078</b>	1019	897
Zinc	ppm ASTM D5185m 1180	<b>1346</b>	1233	1153
Sulfur	ppm ASTM D5185m 2600	<b>3178</b>	3239	2806

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >20	<b>4</b>	2	6
Sodium	ppm ASTM D5185m	<b>&lt;1</b>	2	2
Potassium	ppm ASTM D5185m >20	<b>6</b>	4	9



## INFRA-RED

method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>0.8</b>	0.8	1
Nitration	Abs/cm *ASTM D7624 >20	<b>8.8</b>	8.5	10.0
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>20.3</b>	19.9	23.4

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>15.9</b>	15.4	19.1
Base Number (BN)	mg KOH/g ASTM D2896	<b>6.2</b>	7.2	5.0





# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	12.00	<b>11.1</b>	11.3	11.2

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0103631 **Received** : 12 Jan 2024  
**Lab Number** : 06059013 **Diagnosed** : 12 Jan 2024  
**Unique Number** : 10830395 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**Transervice - Shop 1374 - Berkeley-Hartford**  
 80 International Drive  
 Windsor, CT  
 US 06095  
 Contact: Paul Santanella  
 psantanella@transervice.com  
 T: (860)687-1037  
 F: (860)687-1476

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)