


OIL ANALYSIS REPORT





DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Metal levels are typical for a components first oil change.

Contamination

There is no indication of any contamination in the


Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

| ` | | | | | | |
|---|---|--|--|---|--------------------------|--------------------------|
|) | | | | lan 2024 | | |
| SAMPLE INFOR | MATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | GFL0108327 | | |
| Sample Date | | Client Info | | 06 Jan 2024 | | |
| Machine Age | | Client Info | | 249 | | |
| Oil Age | | Client Info | | 249 | | |
| Oil Changed | | Client Info | | N/A | | |
| Sample Status | | | | NORMAL | | |
| CONTAMINAT | ION | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.1 | NEG | | |
| WEAR METAL | S | method | limit/base | current | history1 | history2 |
| ron | ppm | ASTM D5185m | >50 | 54 | | |
| Chromium | ppm | ASTM D5185m | >4 | <1 | | |
| Nickel | ppm | ASTM D5185m | >2 | 1 | | |
| Гitanium | ppm | ASTM D5185m | | <1 | | |
| Silver | ppm | ASTM D5185m | >3 | <1 | | |
| Aluminum | ppm | ASTM D5185m | | 5 | | |
| _ead | ppm | ASTM D5185m | >30 | <1 | | |
| Copper | ppm | ASTM D5185m | | 19 | | |
| Fin | ppm | ASTM D5185m | >4 | 2 | | |
| /anadium | ppm | ASTM D5185m | | - <1 | | |
| Cadmium | ppm | ASTM D5185m | | 0 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 17 | | |
| Barium | ppm | ASTM D5185m | | 3 | | |
| | ppiii | //OTIVI DOTOOIII | | • | | |
| Molybdenum | ppm | ASTM D5185m | | 54 | | |
| • | | | | - | | |
| Manganese | ppm | ASTM D5185m | | 54 | | |
| Manganese Magnesium | ppm | ASTM D5185m ASTM D5185m | | 54 12 | | |
| Manganese Magnesium Calcium | ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m | | 54 12 786 | | |
| Manganese Magnesium Calcium Phosphorus | ppm ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m | | 54 12 786 1021 | | |
| Manganese Magnesium Calcium Phosphorus Zinc | ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m | | 54 12 786 1021 809 | | |
| Manganese Magnesium Calcium Phosphorus Zinc | ppm ppm ppm ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m | limit/base | 54 12 786 1021 809 933 | | |
| Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN | ppm ppm ppm ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m | | 54 12 786 1021 809 933 2344 | | |
| Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon | ppm ppm ppm ppm ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m | | 54 12 786 1021 809 933 2344 | | |
| Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium | ppm ppm ppm ppm ppm ppm ppm | ASTM D5185m Method ASTM D5185m | >+100 | 54 12 786 1021 809 933 2344 current | history1 | history2 |
| Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium | ppm | ASTM D5185m | >+100 | 54 12 786 1021 809 933 2344 current 34 | history1 | history2 |
| Manganese Magnesium Calcium Phosphorus Zinc Gulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED | ppm | ASTM D5185m | >+100 >20 | 54 12 786 1021 809 933 2344 current 34 5 | history1 | history2 |
| Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot % | ppm | ASTM D5185m | >+100 >20 limit/base | 54 12 786 1021 809 933 2344 current 34 5 | history1 history1 | history2 history2 |
| Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot % Nitration | ppm ppm ppm ppm ppm ppm ppm ppm ppm | ASTM D5185m Method ASTM D5185m | >+100 >20 limit/base >20 | 54 12 786 1021 809 933 2344 current 34 5 11 | history1 history1 | history2 history2 |
| Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot % Nitration | ppm | ASTM D5185m Method ASTM D5185m | >+100 >20 limit/base >20 | 54 12 786 1021 809 933 2344 current 34 5 11 current 0 11.4 | history1 history1 | history2 history2 |
| Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation | ppm | ASTM D5185m Method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D7844 *ASTM D7624 *ASTM D76145 | >+100 >20 limit/base >20 >30 | 54 12 786 1021 809 933 2344 current 34 5 11 current 0 11.4 20.5 | history1 history1 | history2 history2 |




OIL ANALYSIS REPORT



| VISUAL | | method | limit/base | current | history1 | history2 |
|-------------------------|--------|---------|------------|---------|----------|----------|
| White Metal | scalar | *Visual | NONE | NONE | | |
| Yellow Metal | scalar | *Visual | NONE | NONE | | |
| Precipitate | scalar | *Visual | NONE | NONE | | |
| Silt | scalar | *Visual | NONE | NONE | | |
| Debris | scalar | *Visual | NONE | NONE | | |
| Sand/Dirt | scalar | *Visual | NONE | NONE | | |
| Appearance | scalar | *Visual | NORML | NORML | | |
| Odor | scalar | *Visual | NORML | NORML | | |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | | |
| Free Water | scalar | *Visual | | NEG | | |
| FLUID DDODE | DTIES | | | | 111 | 1:: |


| LLUID PROP | EULIES | method | | riistory i | riistoryz |
|--------------|--------|-----------|------|------------|-----------|
| Visc @ 100°C | cSt | ASTM D445 | 14.2 | | |


GRAPHS



Non-ferrous Metals











Certificate L2367

Laboratory Sample No. Test Package : FLEET

Lab Number Unique Number : 10831466

: GFL0108327 : 06060084

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Recieved Diagnosed

: 12 Jan 2024 : 16 Jan 2024 Diagnostician : Wes Davis

GFL Environmental - 652 - Fredericksburg Hauling 10954 Houser Drive

Fredericksburg, VA US 22408

Contact: WILLIAM MILO wmilo@gflenv.com

T:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: