


# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**130084**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 10W30 (--- QTS)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>PCA0115254</b>	PCA0101339	PCA0094256
Sample Date	Client Info		<b>11 Jan 2024</b>	06 Jul 2023	16 Mar 2023
Machine Age	mls	Client Info	<b>76963</b>	39501	18134
Oil Age	mls	Client Info	<b>0</b>	0	0
Oil Changed	Client Info		<b>N/A</b>	Changed	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	<b>32</b>	111	87
Chromium	ppm	ASTM D5185m >20	<b>&lt;1</b>	2	2
Nickel	ppm	ASTM D5185m >4	<b>0</b>	<1	0
Titanium	ppm	ASTM D5185m	<b>0</b>	0	0
Silver	ppm	ASTM D5185m >3	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >20	<b>2</b>	7	14
Lead	ppm	ASTM D5185m >40	<b>&lt;1</b>	3	2
Copper	ppm	ASTM D5185m >330	<b>3</b>	132	187
Tin	ppm	ASTM D5185m >15	<b>1</b>	5	5
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	<1
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	<b>4</b>	11	67
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	<1
Molybdenum	ppm	ASTM D5185m 50	<b>68</b>	64	21
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	2	2
Magnesium	ppm	ASTM D5185m 950	<b>1008</b>	787	193
Calcium	ppm	ASTM D5185m 1050	<b>1164</b>	1238	1059
Phosphorus	ppm	ASTM D5185m 995	<b>1127</b>	1009	796
Zinc	ppm	ASTM D5185m 1180	<b>1346</b>	1286	1022
Sulfur	ppm	ASTM D5185m 2600	<b>3062</b>	2682	2906

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>5</b>	18	36
Sodium	ppm	ASTM D5185m	<b>2</b>	<1	3
Potassium	ppm	ASTM D5185m >20	<b>0</b>	3	3



## INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>1</b>	1.7	1
Nitration	Abs/cm	*ASTM D7624 >20	<b>10.1</b>	13.7	10.8
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>20.5</b>	25.5	23.3

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>17.1</b>	23.8	21.3
Base Number (BN)	mg KOH/g	ASTM D2896	<b>8.6</b>	7.4	6.0









# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	12.00	<b>11.3</b>	11.8	10.2

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0115254 **Recieved** : 16 Jan 2024  
**Lab Number** : 06060680 **Diagnosed** : 16 Jan 2024  
**Unique Number** : 10832062 **Diagnostician** : Wes Davis  
**Test Package** : MOB 1 ( Additional Tests: TBN )

**MILLER TRUCK LEASING #119**  
 39 INDUSTRIAL AVE  
 HASBROUCK HEIGHTS, NJ  
 US 07604  
 Contact: MIKE LONGETTE  
 mlongette@millertransgroup.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (201)528-7053