




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
R98866
Component
Diesel Engine
Fluid
{not provided} (--- GAL)



DIAGNOSIS

Recommendation

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

Metal levels are typical for a new component breaking in.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0090964	GFL0103030	---
Sample Date	Client Info		09 Jan 2024	29 Nov 2023	---
Machine Age	hrs	Client Info	302	133	---
Oil Age	hrs	Client Info	169	133	---
Oil Changed	Client Info		Changed	Changed	---
Sample Status			NORMAL	NORMAL	---

CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.2	NEG	NEG	---
Glycol	WC Method		NEG	NEG	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	31	20	---
Chromium	ppm	ASTM D5185m >20	<1	<1	---
Nickel	ppm	ASTM D5185m >5	11	6	---
Titanium	ppm	ASTM D5185m >2	<1	0	---
Silver	ppm	ASTM D5185m >2	1	0	---
Aluminum	ppm	ASTM D5185m >20	5	4	---
Lead	ppm	ASTM D5185m >40	<1	1	---
Copper	ppm	ASTM D5185m >330	87	31	---
Tin	ppm	ASTM D5185m >15	3	2	---
Vanadium	ppm	ASTM D5185m	0	<1	---
Cadmium	ppm	ASTM D5185m	0	0	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	278	321	---
Barium	ppm	ASTM D5185m	0	<1	---
Molybdenum	ppm	ASTM D5185m	111	98	---
Manganese	ppm	ASTM D5185m	5	3	---
Magnesium	ppm	ASTM D5185m	712	678	---
Calcium	ppm	ASTM D5185m	1357	1355	---
Phosphorus	ppm	ASTM D5185m	731	657	---
Zinc	ppm	ASTM D5185m	847	815	---
Sulfur	ppm	ASTM D5185m	2367	2038	---

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	64	57	---
Sodium	ppm	ASTM D5185m	3	3	---
Potassium	ppm	ASTM D5185m >20	6	6	---
Fuel	%	ASTM D3524 >3.0	<1.0	0.5	---

INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	0.2	0.1	---
Nitration	Abs/cm	*ASTM D7624 >20	8.2	6.6	---
Sulfation	Abs/.1mm	*ASTM D7415 >30	25.1	25.1	---

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	21.4	20.1	---
Base Number (BN)	mg KOH/g	ASTM D2896	8.8	9.8	---







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	9.9	9.6	---

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0090964 **Received** : 17 Jan 2024
Lab Number : **06063391** **Diagnosed** : 19 Jan 2024
Unique Number : 10834773 **Diagnostician** : Don Baldrige
Test Package : FLEET (Additional Tests: FuelDilution)

GFL Environmental - 814 - Little Rock Hauling
 4005 Hwy 161 N.
 Little Rock, AR
 US 72117
 Contact: Michael Lovin
 mlovin@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)