



# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**811060**  
 Component  
**Transmission**  
 Fluid  
 {not provided} (--- GAL)

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The condition of the oil is acceptable for the time in service.

## SAMPLE INFORMATION

|               | method      | limit/base  | current            | history1 | history2 |
|---------------|-------------|-------------|--------------------|----------|----------|
| Sample Number | Client Info |             | <b>GFL0084862</b>  | ---      | ---      |
| Sample Date   | Client Info |             | <b>27 Sep 2023</b> | ---      | ---      |
| Machine Age   | hrs         | Client Info | <b>6127</b>        | ---      | ---      |
| Oil Age       | hrs         | Client Info | <b>6127</b>        | ---      | ---      |
| Oil Changed   | Client Info |             | <b>Changed</b>     | ---      | ---      |
| Sample Status |             |             | <b>NORMAL</b>      | ---      | ---      |

## CONTAMINATION

|       | method    | limit/base | current    | history1 | history2 |
|-------|-----------|------------|------------|----------|----------|
| Water | WC Method | >0.1       | <b>NEG</b> | ---      | ---      |

## WEAR METALS

|          | method | limit/base       | current   | history1 | history2 |
|----------|--------|------------------|-----------|----------|----------|
| Iron     | ppm    | ASTM D5185m >320 | <b>95</b> | ---      | ---      |
| Chromium | ppm    | ASTM D5185m >5   | <b>0</b>  | ---      | ---      |
| Nickel   | ppm    | ASTM D5185m >5   | <b>0</b>  | ---      | ---      |
| Titanium | ppm    | ASTM D5185m      | <b>0</b>  | ---      | ---      |
| Silver   | ppm    | ASTM D5185m      | <b>0</b>  | ---      | ---      |
| Aluminum | ppm    | ASTM D5185m >50  | <b>24</b> | ---      | ---      |
| Lead     | ppm    | ASTM D5185m >65  | <b>24</b> | ---      | ---      |
| Copper   | ppm    | ASTM D5185m >95  | <b>20</b> | ---      | ---      |
| Tin      | ppm    | ASTM D5185m >6   | <b>2</b>  | ---      | ---      |
| Vanadium | ppm    | ASTM D5185m      | <b>0</b>  | ---      | ---      |
| Cadmium  | ppm    | ASTM D5185m      | <b>0</b>  | ---      | ---      |

## ADDITIVES

|            | method | limit/base  | current      | history1 | history2 |
|------------|--------|-------------|--------------|----------|----------|
| Boron      | ppm    | ASTM D5185m | <b>81</b>    | ---      | ---      |
| Barium     | ppm    | ASTM D5185m | <b>0</b>     | ---      | ---      |
| Molybdenum | ppm    | ASTM D5185m | <b>&lt;1</b> | ---      | ---      |
| Manganese  | ppm    | ASTM D5185m | <b>1</b>     | ---      | ---      |
| Magnesium  | ppm    | ASTM D5185m | <b>&lt;1</b> | ---      | ---      |
| Calcium    | ppm    | ASTM D5185m | <b>70</b>    | ---      | ---      |
| Phosphorus | ppm    | ASTM D5185m | <b>246</b>   | ---      | ---      |
| Zinc       | ppm    | ASTM D5185m | <b>0</b>     | ---      | ---      |
| Sulfur     | ppm    | ASTM D5185m | <b>1217</b>  | ---      | ---      |

## CONTAMINANTS




|           | method | limit/base      | current  | history1 | history2 |
|-----------|--------|-----------------|----------|----------|----------|
| Silicon   | ppm    | ASTM D5185m >65 | <b>6</b> | ---      | ---      |
| Sodium    | ppm    | ASTM D5185m     | <b>5</b> | ---      | ---      |
| Potassium | ppm    | ASTM D5185m >20 | <b>2</b> | ---      | ---      |

## VISUAL

|                  | method | limit/base    | current      | history1 | history2 |
|------------------|--------|---------------|--------------|----------|----------|
| White Metal      | scalar | *Visual NONE  | <b>NONE</b>  | ---      | ---      |
| Yellow Metal     | scalar | *Visual NONE  | <b>NONE</b>  | ---      | ---      |
| Precipitate      | scalar | *Visual NONE  | <b>NONE</b>  | ---      | ---      |
| Silt             | scalar | *Visual NONE  | <b>NONE</b>  | ---      | ---      |
| Debris           | scalar | *Visual NONE  | <b>NONE</b>  | ---      | ---      |
| Sand/Dirt        | scalar | *Visual NONE  | <b>NONE</b>  | ---      | ---      |
| Appearance       | scalar | *Visual NORML | <b>NORML</b> | ---      | ---      |
| Odor             | scalar | *Visual NORML | <b>NORML</b> | ---      | ---      |
| Emulsified Water | scalar | *Visual >0.1  | <b>NEG</b>   | ---      | ---      |
| Free Water       | scalar | *Visual       | <b>NEG</b>   | ---      | ---      |



# OIL ANALYSIS REPORT







## FLUID PROPERTIES

| method      | limit/base    | current | history1 | history2 |
|-------------|---------------|---------|----------|----------|
| Visc @ 40°C | cSt ASTM D445 | 39.1    | ---      | ---      |

## SAMPLE IMAGES

| method | limit/base | current  | history1 | history2 |
|--------|------------|----------|----------|----------|
| Color  |            | no image | no image | no image |
| Bottom |            | no image | no image | no image |

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0084862 **Received** : 17 Jan 2024  
**Lab Number** : 06063939 **Diagnosed** : 22 Jan 2024  
**Unique Number** : 10835321 **Diagnostician** : Don Baldrige  
**Test Package** : FLEET ( Additional Tests: FT-IR, KV100, TBN )

**GFL Environmental - 959A - Urbana HC**  
 4808 cunningham Rd  
 Urbana, IL  
 US 61802  
 Contact: Kristine Tryon  
 Ktryon@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: