




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Area  
**(64837P)**

Machine Id  
**3771**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (10 GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0093769</b>	GFL0079020	GFL0079032
Sample Date	Client Info		<b>15 Jan 2024</b>	01 Nov 2023	27 Jul 2023
Machine Age	hrs	Client Info	<b>14496</b>	14077	13560
Oil Age	hrs	Client Info	<b>0</b>	0	0
Oil Changed	Client Info		<b>Changed</b>	Changed	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >165	<b>4</b>	8	4
Chromium	ppm	ASTM D5185m >5	<b>0</b>	<1	<1
Nickel	ppm	ASTM D5185m >4	<b>0</b>	<1	<1
Titanium	ppm	ASTM D5185m >2	<b>0</b>	<1	0
Silver	ppm	ASTM D5185m >2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >20	<b>&lt;1</b>	2	1
Lead	ppm	ASTM D5185m >150	<b>2</b>	3	1
Copper	ppm	ASTM D5185m >90	<b>&lt;1</b>	2	<1
Tin	ppm	ASTM D5185m >5	<b>&lt;1</b>	<1	0
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	<1	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>4</b>	3	8
Barium	ppm	ASTM D5185m 0	<b>0</b>	5	1
Molybdenum	ppm	ASTM D5185m 60	<b>57</b>	58	57
Manganese	ppm	ASTM D5185m 0	<b>0</b>	<1	0
Magnesium	ppm	ASTM D5185m 1010	<b>952</b>	859	851
Calcium	ppm	ASTM D5185m 1070	<b>1049</b>	1045	1120
Phosphorus	ppm	ASTM D5185m 1150	<b>1027</b>	1034	987
Zinc	ppm	ASTM D5185m 1270	<b>1244</b>	1187	1197
Sulfur	ppm	ASTM D5185m 2060	<b>2886</b>	2969	2900

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >35	<b>4</b>	7	4
Sodium	ppm	ASTM D5185m	<b>3</b>	1	<1
Potassium	ppm	ASTM D5185m >20	<b>0</b>	2	<1

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >7.5	<b>0.2</b>	0.3	0.1
Nitration	Abs/cm	*ASTM D7624 >20	<b>7.0</b>	8.1	6.2
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>18.7</b>	19.8	18.2

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>14.7</b>	15.9	13.7
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>7.8</b>	7.4	7.8







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>12.9</b>	12.8	13.1

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0093769 **Recieved** : 18 Jan 2024  
**Lab Number** : **06064718** **Diagnosed** : 19 Jan 2024  
**Unique Number** : 10836100 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 029 - Wytheville**  
 2390 North 4th Street  
 Wytheville, VA  
 US 24382  
 Contact: CHARLES CORVIN  
 charles.corvin@gflenv.com; canastasio@wearcheckusa.com  
 T: (276)223-4476  
 F: (276)223-1283

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)