

## **OIL ANALYSIS REPORT**

Sample Rating Trend

NORMAL

Area {UNASSIGNED} **Dt43** Component Fluic

Transmission (Auto)

DEXRON III (37 QTS)

### DIAGNOSIS

4 

#### Recommendation

Resample at the next service interval to monitor. ( Customer Sample Comment: Dt43)

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the fluid.

#### Fluid Condition

The condition of the fluid is acceptable for the time in service.


ad	limit/bass	ourropt	I
	Jan20	24	



				Jan2024		
SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0116133		
Sample Date		Client Info		12 Jan 2024		
Machine Age	mls	Client Info		30227		
Oil Age	mls	Client Info		75000		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATI	ON	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS	6	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>220	73		
Chromium	ppm	ASTM D5185m	>2	0		
Nickel	ppm	ASTM D5185m	>5	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m	>5	0		
Aluminum	ppm	ASTM D5185m	>75	25		
Lead	ppm	ASTM D5185m	>95	7		
Copper	ppm	ASTM D5185m	>60	25		
Tin	ppm	ASTM D5185m	>10	5		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
	PP			-		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		57		
Barium	ppm	ASTM D5185m		<1		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		2		
Magnesium	ppm	ASTM D5185m		<1		
Calcium	ppm	ASTM D5185m		120		
Phosphorus	ppm	ASTM D5185m		221		
Zinc	ppm	ASTM D5185m		0		
Sulfur	ppm	ASTM D5185m		1723		
CONTAMINAN	ΓS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	6		
Sodium	ppm	ASTM D5185m		5		
Potassium	ppm	ASTM D5185m	>20	6		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
		10000				
		*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Precipitate Silt	scalar scalar	*Visual	NONE	NONE		
Precipitate Silt Debris	scalar scalar scalar	*Visual *Visual	NONE NONE	NONE		
Precipitate Silt Debris Sand/Dirt	scalar scalar scalar scalar	*Visual *Visual *Visual	NONE NONE NONE	NONE NONE NONE		
Precipitate Silt Debris Sand/Dirt Appearance	scalar scalar scalar scalar scalar	*Visual *Visual *Visual *Visual	NONE NONE NORML	NONE NONE NONE NORML	  	
Precipitate Silt Debris Sand/Dirt Appearance Odor	scalar scalar scalar scalar scalar scalar	*Visual *Visual *Visual *Visual *Visual	NONE NONE NORML NORML	NONE NONE NORML NORML		
Precipitate Silt Debris Sand/Dirt Appearance	scalar scalar scalar scalar scalar	*Visual *Visual *Visual *Visual	NONE NONE NORML	NONE NONE NONE NORML	  	  



# **OIL ANALYSIS REPORT**



	FLUID PROPE	ERTIES	method	limit/base	current	history1	history2
-	Visc @ 40°C	cSt	ASTM D445	35.0	32.3		
	SAMPLE IMAG	GES	method	limit/base	current	history1	history2
	Color				no image	no image	no image
Jan 12/24	Bottom				no image	no image	no image
	GRAPHS						
	Ferrous Alloys	hls		Jan1224			
	Viscosity @ 40°C			224			
Laboratory Sample No. Lab Number Unique Number Test Package liscuss this sample report, c enotes test methods that a	: 06065237 : 10836619 : FLEET contact Customer Serv	Recieved Diagnosed Diagnostic	:18 d :22 cian :Sea 20-237-1369	lan 2024 lan 2024 n Felton		400 WEST C Contact: GEOR	K STEELE IN N PARSON S COLUMBIA, S US 2911 GE EDWARE @nwwhite.cc

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: