


OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

 Machine Id
M7 (S/N 1457487)

 Component
Biogas Engine

 Fluid
PETRO CANADA SENTRON LD 8000 (--- GAL)
DIAGNOSIS
Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

Fuel content negligible. There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0106201	PCA0106196	PCA0106188
Sample Date	Client Info		06 Jan 2024	15 Dec 2023	20 Nov 2023
Machine Age	hrs	Client Info	9089	8589	8088
Oil Age	hrs	Client Info	0	5790	4789
Oil Changed	Client Info		N/A	Changed	N/A
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.1	NEG	NEG	NEG
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>45	17	12
Chromium	ppm	ASTM D5185m	>2	1	<1
Nickel	ppm	ASTM D5185m	>2	<1	0
Titanium	ppm	ASTM D5185m		<1	0
Silver	ppm	ASTM D5185m	>5	0	0
Aluminum	ppm	ASTM D5185m	>10	2	2
Lead	ppm	ASTM D5185m	>5	3	3
Copper	ppm	ASTM D5185m	>14	<1	0
Tin	ppm	ASTM D5185m	>13	2	1
Vanadium	ppm	ASTM D5185m		0	0
Cadmium	ppm	ASTM D5185m		<1	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		<1	0
Barium	ppm	ASTM D5185m		0	0
Molybdenum	ppm	ASTM D5185m		1	0
Manganese	ppm	ASTM D5185m		<1	<1
Magnesium	ppm	ASTM D5185m		11	13
Calcium	ppm	ASTM D5185m	1351	1794	1805
Phosphorus	ppm	ASTM D5185m	302	369	336
Zinc	ppm	ASTM D5185m	358	443	440
Sulfur	ppm	ASTM D5185m	2758	3594	3242

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>200	3	3
Sodium	ppm	ASTM D5185m		10	13
Potassium	ppm	ASTM D5185m	>20	2	3
Fuel	%	ASTM D3524	>4.0	0.0	0.0

INFRA-RED


	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844		0.1	0.1
Nitration	Abs/cm	*ASTM D7624	>20	7.1	6.8
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.6	22.9

FLUID DEGRADATION


	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	17.3	17.5
Acid Number (AN)	mg KOH/g	ASTM D8045	0.86	2.34	1.76
Base Number (BN)	mg KOH/g	ASTM D2896	4.64	3.15	3.39

OIL ANALYSIS REPORT


Fuel Dilution




Acid Number



Base Number



Viscosity @ 100°C




VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG


FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	13.3	14.2	14.1	14.1

GRAPHS


Iron (ppm)




Lead (ppm)




Aluminum (ppm)




Chromium (ppm)




Copper (ppm)




Silicon (ppm)



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0106201 **Received** : 22 Jan 2024
Lab Number : 06066965 **Tested** : 24 Jan 2024
Unique Number : 10843642 **Diagnosed** : 04 Feb 2024 - Doug Bogart
Test Package : MOB 2 (Additional Tests: FuelDilution, PercentFuel)

AMERICAN PETROLEUM
 CARR 865 KM 0.2 CAMPANILA
 TOA BAJA, PR
 US 00949
 Contact: NEFTALI ORTIZ
 nortiz@americanpetroleumpr.com
 T: (787)794-1985

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: