




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**813055**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0103886</b>	GFL0097345	GFL0097365
Sample Date	Client Info		<b>16 Jan 2024</b>	30 Oct 2023	04 Oct 2023
Machine Age	hrs	Client Info	<b>1519</b>	574	574
Oil Age	hrs	Client Info	<b>430</b>	574	574
Oil Changed	Client Info		<b>Not Chngd</b>	Changed	N/A
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	<b>12</b>	22	21
Chromium	ppm	ASTM D5185m >20	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m >5	<b>4</b>	6	6
Titanium	ppm	ASTM D5185m >2	<b>0</b>	0	0
Silver	ppm	ASTM D5185m >2	<b>0</b>	2	2
Aluminum	ppm	ASTM D5185m >20	<b>&lt;1</b>	2	0
Lead	ppm	ASTM D5185m >40	<b>0</b>	<1	<1
Copper	ppm	ASTM D5185m >330	<b>7</b>	66	67
Tin	ppm	ASTM D5185m >15	<b>&lt;1</b>	1	1
Vanadium	ppm	ASTM D5185m	<b>&lt;1</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>4</b>	9	6
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m 60	<b>56</b>	61	67
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	1	1
Magnesium	ppm	ASTM D5185m 1010	<b>928</b>	882	923
Calcium	ppm	ASTM D5185m 1070	<b>1075</b>	1019	1039
Phosphorus	ppm	ASTM D5185m 1150	<b>1007</b>	960	971
Zinc	ppm	ASTM D5185m 1270	<b>1221</b>	1181	1228
Sulfur	ppm	ASTM D5185m 2060	<b>2942</b>	2340	2932

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>4</b>	11	10
Sodium	ppm	ASTM D5185m	<b>2</b>	5	3
Potassium	ppm	ASTM D5185m >20	<b>2</b>	3	2

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	<b>0.5</b>	0.7	0.6
Nitration	Abs/cm	*ASTM D7624 >20	<b>8.3</b>	9.0	8.2
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>19.4</b>	21.0	20.3

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>15.4</b>	17.4	16.5
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>7.1</b>	7.0	7.6







# OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.6</b>	13.5

## GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
 Sample No. : GFL0103886      Recieved : 22 Jan 2024  
 Lab Number : **06067472**      Diagnosed : 23 Jan 2024  
 Unique Number : 10844149      Diagnostician : Wes Davis  
 Test Package : FLEET

**GFL Environmental - 654S - Midlothian**  
 12230 Deergrove Road  
 Midlothian, VA  
 US 23112  
 Contact: Corbin Umphlet  
 cumphlet@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: