


OIL ANALYSIS REPORT

(65351Z) Walgreens - Tractor [Walgreens - Tractor] 136A624151

Diesel Engine

PETRO CANADA DURON SHP 10W30 (11 GAL)



DIAGNOSIS

Recommendation

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

Metal levels are typical for a new component breaking in.

Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.


Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

GAL)				Jan 2024		
SAMPLE INFORI	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0115814		
Sample Date		Client Info		18 Jan 2024		
Machine Age	mls	Client Info		58006		
Oil Age	mls	Client Info		58006		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINAT	ION	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0		
Water		WC Method	>0.2	NEG		
Glycol		WC Method		NEG		
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>80	83		
Chromium	ppm	ASTM D5185m	>5	4		
Nickel	ppm	ASTM D5185m	>2	<1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m	>3	0		
Aluminum	ppm	ASTM D5185m	>30	54		
Lead	ppm	ASTM D5185m	>30	<1		
Copper	ppm		>150	153		
Tin	ppm	ASTM D5185m	>5	4		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	25		
Barium	ppm	ASTM D5185m	0	<1		
Molybdenum	ppm	ASTM D5185m	50	40		
Manganese	ppm	ASTM D5185m	0	7		
Magnesium	ppm	ASTM D5185m	950	576		
Calcium	ppm	ASTM D5185m	1050	1771		
Phosphorus	ppm	ASTM D5185m	995	718		
Zinc	ppm	ASTM D5185m	1180	912		
Sulfur	ppm	ASTM D5185m	2600	1903		
CONTAMINAN		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	9		
Sodium	ppm	ASTM D5185m	00	7		
Potassium	ppm	ASTM D5185m		144		
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.9		
Nitration	Abs/cm	*ASTM D7624	>20	11.2		
Sulfation	Abs/.1mm	*ASTM D7415	>30	23.5		
FLUID DEGRA		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	25.6		
Base Number (BN)	mg KOH/g	ASTM D2896		5.8		




OIL ANALYSIS REPORT





VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.2	NEG		
Free Water	scalar	*Visual		NEG		


FLUID PROP	ERIIES	method	ilmit/base	current	nistory i	nistory2
Visc @ 100°C	cSt	ASTM D445	12.00	10.5		



Non-ferrous Metals











Certificate L2367

Laboratory Sample No. Lab Number Test Package : FLEET

Unique Number : 10845630

: PCA0115814 : 06068953

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Recieved Diagnosed

: 23 Jan 2024 : 25 Jan 2024 Diagnostician : Sean Felton

Transervice - Shop 1370 - Berkeley-Perrysburg 28727 Oregon Road

Perrysburg, OH US 43551 Contact: Curtis Hart

chart@transervice.com T: (419)666-3277

F: (419)666-3279

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)