

OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



3793C AUTOCAR ACX

Component

Natural Gas Engine

PETRO CANADA DURON GEO LD 15W40 (48 QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil

Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.


(48 QTS)						
SAMPLE INFOR	RMATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0103165	GFL0103241	GFL0094684
Sample Date		Client Info		23 Jan 2024	28 Dec 2023	03 Oct 2023
Machine Age	hrs	Client Info		16038	15821	15178
Oil Age	hrs	Client Info		217	696	53
Oil Changed		Client Info		Changed	Changed	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINA	TION	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	NEG
WEAR META	LS	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	8	13	11
Chromium	ppm	ASTM D5185m	>4	1	3	2
Nickel	ppm	ASTM D5185m	>2	<1	0	0
Titanium	ppm	ASTM D5185m		<1	<1	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>9	1	3	3
Lead	ppm	ASTM D5185m	>30	<1	2	2
Copper	ppm	ASTM D5185m	>35	1	4	5
Tin	ppm	ASTM D5185m	>4	<1	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	<1
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	50	28	9	7
Barium	ppm	ASTM D5185m	5	0	0	0
Molybdenum	ppm	ASTM D5185m	50	52	53	57
Manganese	ppm	ASTM D5185m	0	<1	<1	<1
Magnesium	ppm	ASTM D5185m	560	566	570	631
Calcium	ppm	ASTM D5185m	1510	1486	1661	1795
Phosphorus	ppm	ASTM D5185m	780	762	687	753
Zinc	ppm	ASTM D5185m	870	958	1034	1061
Sulfur	ppm	ASTM D5185m	2040	2449	2333	2293
CONTAMINAL	NTS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>+100	8	5	6
Sodium	ppm	ASTM D5185m		1	5	7
Potassium	ppm	ASTM D5185m	>20	4	2	1
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844		0	0	0
Nitration	Abs/cm	*ASTM D7624	>20	7.7	11.0	10.6
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.2	22.8	22.5
FLUID DEGRA	DATION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	16.3	19.7	19.6
D 11						

Base Number (BN) mg KOH/g ASTM D2896 10.2 7.7



OIL ANALYSIS REPORT







VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	LIGHT
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROPE	RTIES	method				history2
Visc @ 100°C	cSt	ASTM D445	15.1	14.7	15.2	15.2

GRAPHS

Ferrous Alloys 20 E 15











Certificate L2367

Laboratory Sample No. Lab Number Test Package : FLEET

Unique Number

: GFL0103165 : 06069355

: 10846032

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Recieved : 24 Jan 2024

Diagnosed Diagnostician : Wes Davis

: 24 Jan 2024

3741 Conquest Drive Garner, NC US 27529 Contact: Craig Johnson

GFL Environmental - 001 - Raleigh(CNG)

craig.johnson@gflenv.com T: (919)662-7100 F: (919)662-7130

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: GFL001 [WUSCAR] 06069355 (Generated: 01/24/2024 16:52:06) Rev: 1

Submitted By: Craig Johnson