

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



FREIGHTLINER 425125-SW4403

Component **Diesel Engine**

MOBIL DELVAC 1300 SUPER15W40 (--- GAL)



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

OI EIII3W40 (- GAL)		May2023	Dec2023		
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0095484	GFL0077254	
Sample Date		Client Info		27 Dec 2023	05 May 2023	
Machine Age	hrs	Client Info		15896	14881	
Oil Age	hrs	Client Info		500	556	
Oil Changed		Client Info		Changed	Changed	
Sample Status				NORMAL	NORMAL	
CONTAMINAT	ION	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0	<1.0	
Water		WC Method	>0.2	NEG	NEG	
Glycol		WC Method		NEG	NEG	
WEAR METAL	.S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>80	18	17	
Chromium	ppm	ASTM D5185m	>5	<1	<1	
Nickel	ppm	ASTM D5185m	>2	0	<1	
Titanium	ppm	ASTM D5185m		0	<1	
Silver	ppm	ASTM D5185m	>3	0	0	
Aluminum	ppm	ASTM D5185m	>30	6	3	
Lead	ppm	ASTM D5185m	>30	<1	0	
Copper	ppm	ASTM D5185m	>150	3	3	
Tin	ppm	ASTM D5185m	>5	<1	<1	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	68	51	
Barium	ppm	ASTM D5185m	0	0	0	
Molybdenum	ppm	ASTM D5185m	0	117	92	
Manganese	ppm	ASTM D5185m		<1	<1	
Magnesium	ppm	ASTM D5185m	0	674	638	
Calcium	ppm	ASTM D5185m		1220	1504	
Phosphorus	ppm	ASTM D5185m		707	739	
Zinc	ppm	ASTM D5185m		797	938	
Sulfur	ppm	ASTM D5185m		3024	3462	
CONTAMINAN	ITS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	7	6	
Sodium	ppm	ASTM D5185m		2	2	
Potassium	ppm	ASTM D5185m	>20	3	5	
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.5	0.6	
Nitration	Abs/cm	*ASTM D7624	>20	9.6	10.1	
Sulfation	Abs/.1mm	*ASTM D7415	>30	18.9	20.1	
FLUID DEGRAI	NATION	method	limit/base		hioton/1	history2
	DATION	memod	IIIIII/Dase	current	history1	HISTOLYZ
Oxidation	Abs/.1mm	*ASTM D7414	>25	15.6	17.5	




OIL ANALYSIS REPORT





VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	NONE	NONE	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	
Free Water	scalar	*Visual		NEG	NEG	
	DTIES				111	1:


		memou			HISTOLAL	HISTOLYZ
Visc @ 100°C	cSt	ASTM D445	14	14.1	14.2	

GRAPHS











Certificate L2367

Laboratory Sample No. Lab Number

Unique Number : 10846531 Test Package : FLEET

: GFL0095484 : 06069854

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Recieved Diagnosed

: 24 Jan 2024 : 25 Jan 2024 Diagnostician : Wes Davis

GFL Environmental - 981 - Port Arthur Hauling

1000 S Business Park Dr Port Arthur, TX US 77640 Contact: MICHAEL KAY

mkay@gflenv.com T: (336)660-9331

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)