


OIL ANALYSIS REPORT

Sample Rating Trend



WEAR



Machine Id **413024**

Component **Diesel Engine**

PETRO CANADA DURON SHP 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear

Valve wear is indicated. All other component wear rates are normal.

Contamination

There is no indication of any contamination in the oil


Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.


ov2022 Feb2023 May2023 Jun2023 Aug2023 Ov2023 Ov2023							
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2	
Sample Number		Client Info		GFL0046914	GFL0090977	GFL0103023	
Sample Date		Client Info		19 Jan 2024	28 Dec 2023	05 Dec 2023	
Machine Age	hrs	Client Info		3088	3009	2869	
Oil Age	hrs	Client Info		79	140	132	
Oil Changed		Client Info		Changed	Changed	Changed	
Sample Status				ABNORMAL	ABNORMAL	NORMAL	
CONTAMINAT	ION	method	limit/base	current	history1	history2	
-uel		WC Method	>5	<1.0	<1.0	<1.0	
<i>N</i> ater		WC Method	>0.2	NEG	NEG	NEG	
Glycol		WC Method		NEG	NEG	NEG	
WEAR METAL	S	method	limit/base	current	history1	history2	
ron	ppm	ASTM D5185m	>100	10	7	3	
Chromium	ppm	ASTM D5185m	>20	1	<1	0	
Nickel	ppm	ASTM D5185m	>4	<u>^</u> 6	<u> </u>	4	
Γitanium	ppm	ASTM D5185m		<1	<1	0	
Silver	ppm	ASTM D5185m	>3	0	0	0	
Aluminum	ppm	ASTM D5185m	>20	4	2	2	
_ead	ppm	ASTM D5185m	>40	<1	<1	<1	
Copper	ppm	ASTM D5185m	>330	4	2	1	
Γin	ppm	ASTM D5185m	>15	1	<1	0	
/anadium	ppm	ASTM D5185m		0	0	0	
Cadmium	ppm	ASTM D5185m		<1	0	0	
ADDITIVES		method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m	0	2	4	1	
Barium	ppm	ASTM D5185m	0	0	0	0	
Molybdenum	ppm	ASTM D5185m	60	57	59	56	
Manganese	ppm	ASTM D5185m	0	<1	<1	0	
Magnesium	ppm	ASTM D5185m	1010	931	1032	1028	
Calcium	ppm	ASTM D5185m	1070	1007	1111	1121	
Phosphorus	ppm	ASTM D5185m	1150	990	1070	1135	
Zinc	ppm	ASTM D5185m	1270	1203	1315	1263	
Sulfur	ppm	ASTM D5185m	2060	3092	3194	3216	
CONTAMINAN	ITS	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m	>25	7	6	6	
Sodium	ppm	ASTM D5185m		4	2	<1	
Potassium	ppm	ASTM D5185m	>20	6	4	4	
INFRA-RED		method	limit/base	current	history1	history2	
Soot %	%	*ASTM D7844	>3	0.3	0.2	0.2	
Nitration	Abs/cm	*ASTM D7624		8.4	7.8	6.9	
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.2	19.2	18.6	
FLUID DEGRA	OATION	method	limit/base	current	history1	history2	
Oxidation	Abs/.1mm	*ASTM D7414	>25	15.6	15.5	15.0	
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	7.4	7.7	7.6	



OIL ANALYSIS REPORT




	N	正	Mar	Jun	Aug	Oct	Dec
10.		Numbe	r				
(B/H0	0 ~	-	/	\		^	_
y Bu).	0-					\vee	
Base Number (mg KOH/g)	0						
eg 2.	0						
0.	ov8/22	sb2/23	ay2/23	128/23	123/23	t19/23	28/22





VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROPI	EKIIES	method	ilmit/base	current	nistory i	nistory2
Visc @ 100°C	cSt	ASTM D445	15.4	13.7	13.8	14.2

GRAPHS













Certificate L2367

Laboratory Sample No. Lab Number Test Package : FLEET

: 06070939 Unique Number : 10847616

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : GFL0046914 Recieved : 25 Jan 2024

Diagnosed : 29 Jan 2024 Diagnostician : Don Baldridge GFL Environmental - 814 - Little Rock Hauling

4005 Hwy 161 N. Little Rock, AR US 72117

Contact: Brad Manager

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:

F: