




OIL ANALYSIS REPORT

Area
(BB31712)
Machine Id
928023-1120
Component
Diesel Engine
Fluid
TIER ONE 15W40 (--- GAL)

Sample Rating Trend



NORMAL



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2	
Sample Number	Client Info	GFL0102213	GFL0047357	GFL0018786	
Sample Date	Client Info	22 Jan 2024	07 Mar 2022	20 Jul 2021	
Machine Age	hrs	Client Info	14626	10583	9423
Oil Age	hrs	Client Info	600	1160	620
Oil Changed	Client Info	Changed	Changed	Changed	
Sample Status		NORMAL	NORMAL	NORMAL	

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >3.0	<1.0	<1.0	<1.0
Water	WC Method >0.2	NEG	NEG	NEG
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >120	5	42	29
Chromium	ppm ASTM D5185m >20	<1	1	1
Nickel	ppm ASTM D5185m >5	<1	0	<1
Titanium	ppm ASTM D5185m >2	<1	<1	<1
Silver	ppm ASTM D5185m >2	0	0	0
Aluminum	ppm ASTM D5185m >20	4	4	6
Lead	ppm ASTM D5185m >40	<1	8	1
Copper	ppm ASTM D5185m >330	<1	4	4
Tin	ppm ASTM D5185m >15	<1	3	1
Antimony	ppm ASTM D5185m	---	---	0
Vanadium	ppm ASTM D5185m	<1	0	0
Cadmium	ppm ASTM D5185m	<1	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m	5	7	18
Barium	ppm ASTM D5185m	0	0	0
Molybdenum	ppm ASTM D5185m	53	92	41
Manganese	ppm ASTM D5185m	<1	<1	<1
Magnesium	ppm ASTM D5185m	854	255	540
Calcium	ppm ASTM D5185m	1021	2121	1621
Phosphorus	ppm ASTM D5185m	919	1018	909
Zinc	ppm ASTM D5185m	1155	1307	1147
Sulfur	ppm ASTM D5185m	3022	2699	2475

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	5	10	10
Sodium	ppm ASTM D5185m	8	0	5
Potassium	ppm ASTM D5185m >20	3	3	15

INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >4	0.2	1.3	2.1
Nitration	Abs/cm *ASTM D7624 >20	6.6	13.4	10.7
Sulfation	Abs/.1mm *ASTM D7415 >30	18.4	27.6	24.5

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	14.0	20.3	14.8
Base Number (BN)	mg KOH/g ASTM D2896	8.1	5.9	7.3







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	13.4	14.0	13.4

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0102213 **Received** : 25 Jan 2024
Lab Number : **06070981** **Diagnosed** : 26 Jan 2024
Unique Number : 10847658 **Diagnostician** : Wes Davis
Test Package : FLEET

GFL Environmental - 638 - Greenville
 4102 Industrial Pkwy
 Harrison, MI
 US 48625
 Contact: NORM GWISDALLA
 ngwisdalla@gflenv.com
 T:
 F:

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)