




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Area  
**020**  
Machine Id  
**813002**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (38)**



## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0103808</b>	GFL0076959	GFL0091172
Sample Date	Client Info	<b>22 Jan 2024</b>	31 Oct 2023	14 Sep 2023
Machine Age	hrs	<b>3827</b>	3033	0
Oil Age	hrs	<b>794</b>	3033	600
Oil Changed	Client Info	<b>Changed</b>	Changed	Not Changed
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >120	<b>14</b>	14	12
Chromium	ppm ASTM D5185m >20	<b>&lt;1</b>	<1	<1
Nickel	ppm ASTM D5185m >5	<b>2</b>	3	2
Titanium	ppm ASTM D5185m >2	<b>&lt;1</b>	0	<1
Silver	ppm ASTM D5185m >2	<b>0</b>	<1	0
Aluminum	ppm ASTM D5185m >20	<b>&lt;1</b>	1	1
Lead	ppm ASTM D5185m >40	<b>&lt;1</b>	<1	<1
Copper	ppm ASTM D5185m >330	<b>2</b>	2	2
Tin	ppm ASTM D5185m >15	<b>1</b>	<1	1
Vanadium	ppm ASTM D5185m	<b>&lt;1</b>	<1	<1
Cadmium	ppm ASTM D5185m	<b>0</b>	<1	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>3</b>	2	3
Barium	ppm ASTM D5185m 0	<b>0</b>	4	0
Molybdenum	ppm ASTM D5185m 60	<b>59</b>	56	59
Manganese	ppm ASTM D5185m 0	<b>&lt;1</b>	<1	<1
Magnesium	ppm ASTM D5185m 1010	<b>890</b>	831	1015
Calcium	ppm ASTM D5185m 1070	<b>1111</b>	995	1199
Phosphorus	ppm ASTM D5185m 1150	<b>968</b>	774	1028
Zinc	ppm ASTM D5185m 1270	<b>1181</b>	1118	1329
Sulfur	ppm ASTM D5185m 2060	<b>2608</b>	2626	3677

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>3</b>	4	4
Sodium	ppm ASTM D5185m	<b>4</b>	2	7
Potassium	ppm ASTM D5185m >20	<b>1</b>	2	7

## INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >4	<b>0.6</b>	0.6	0.5
Nitration	Abs/cm *ASTM D7624 >20	<b>8.5</b>	7.7	7.8
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>19.3</b>	18.7	18.6

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>15.5</b>	14.1	14.1
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>7.1</b>	8.8	8.1







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.6</b>	13.9	13.9

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0103808 **Received** : 26 Jan 2024  
**Lab Number** : **06071373** **Diagnosed** : 26 Jan 2024  
**Unique Number** : 10848050 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 020 - Alamance**  
 703 East Gilbreath St  
 Graham, NC  
 US 27253  
 Contact: JEREMY SHORES  
 jeremy.shores@gflenv.com  
 T: (336)668-3712  
 F: (336)229-0526

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)